# **Contact Sheet**



# Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

# **North America**





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

# **Africa**



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

# Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand


Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

# **Sparex Export Markets**



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



# SAFETY DATA SHEET QUALUBE SYNTOGEAR TDL 80W90

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name QUALUBE SYNTOGEAR TDL 80W90

Product number TDL80W90

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Gear oil.

1.3. Details of the supplier of the safety data sheet

Supplier WITHAM OIL AND PAINT LTD

**OUTER CIRCLE ROAD** 

LINCOLN LN2 4HL 01522 521192 01522 537030 01522 560228

enquires@withamgroup.co.uk

Manufacturer WITHAM OIL AND PAINT LTD

**OUTER CIRCLE ROAD** 

LINCOLN LN2 4HL 01522 521192 01522 537030 01522 560228

enquires@withamgroup.co.uk

1.4. Emergency telephone number

Emergency telephone (01522) 521192 Monday to Thursday 8.00am to 5.00pm, Friday 8.00am to 4.30pm.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Skin Sens. 1 - H317

Environmental hazards Not Classified

Classification (67/548/EEC or -

1999/45/EC)

2.2. Label elements

#### **QUALUBE SYNTOGEAR TDL 80W90**

#### **Pictogram**



Signal word Warning

Hazard statements H317 May cause an allergic skin reaction.

**Precautionary statements** P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P501 Dispose of contents/container in accordance with national regulations.

Contains Polysulfides, di-tert-Bu, Reaction products of 4-methyl-2-pentanol and diphosphorous

pentasulfide, propoxylated, esterified with diphosphorous pentaoxide and salted by amines,

C12-14-tert-alkyl

Supplementary precautionary

P261 Avoid breathing vapour/spray.

statements P272 Contaminated work clothing should not be allowed out of the workplace.

#### 2.3. Other hazards

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH annex XIII.

# SECTION 3: Composition/information on ingredients

# 3.2. Mixtures

NON CLASSIFIED COMPONENT		60-100%
CAS number: —		
Classification Not Classified	Classification (67/548/EEC or 1999/45/EC)	

Polysulfides, di-tert-Bu 1-5%

CAS number: 68937-96-2 EC number: 273-103-3

Classification

Skin Sens. 1B - H317 Aquatic Chronic 3 - H412

Mineral oil 1-5%

CAS number: —

Classification Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 Xn; R65

# **QUALUBE SYNTOGEAR TDL 80W90**

Reaction products of 4-methyl-2-pentanol and diphosphorous pentasulfide,propoxylated,esterified with diphosphorous pentaoxide and salted by amines, C12-14-tert-alkyl

<1%

CAS number: — EC number: 931-384-6

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 4 - H302 Xn; R22. Xi; R41. N; R51/53. R43

Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

O,O,O-triphenyl phosphorothioate

<1%

CAS number: 597-82-0 EC number: 209-909-9

Classification Classification (67/548/EEC or 1999/45/EC)

Repr. 2 - H361 Repr. Cat. 3 R62, R63. R52/53

Aquatic Chronic 3 - H412

1,3,4 Thiadiazolidine-2,5-dithione, reaction products with

<1%

hydrogen peroxide and tert-nonanethiol

Classification Classification (67/548/EEC or 1999/45/EC)

Aquatic Chronic 3 - H412 R52/53

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

# SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General information** Remove affected person from source of contamination.

Inhalation Remove affected person from source of contamination. For those providing assistance, avoid

exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If

breathing stops, provide artificial respiration.

**Ingestion** Get medical attention. Do not induce vomiting.

Skin contact Wash skin thoroughly with soap and water. If product is injected into or under the skin, or into

any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment

within the first few hours may significantly reduce the ultimate extent of injury.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

## 4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

#### **QUALUBE SYNTOGEAR TDL 80W90**

**Inhalation** Vapours may cause headache, fatigue, dizziness and nausea.

**Ingestion** Harmful: May cause lung damage if swallowed.

**Skin contact** Prolonged contact may cause redness, irritation and dry skin.

**Eye contact** Irritation of eyes and mucous membranes.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat

appropriately.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2). Thermal

decomposition or combustion products may include the following substances: Toxic gases or

vapours.

Hazardous combustion

products

Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Aldehydes, Sulphur oxides, Incomplete combustion products, Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during

firefighting

Evacuate area. Control run-off water by containing and keeping it out of sewers and

watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

# SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions**Wear protective clothing as described in Section 8 of this safety data sheet.

## 6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the

Environmental Agency or other appropriate regulatory body. Do not discharge into drains or

watercourses or onto the ground.

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up**Absorb spillage with non-combustible, absorbent material.

# 6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

# SECTION 7: Handling and storage

# 7.1. Precautions for safe handling

Usage precautions Static electricity and formation of sparks must be prevented. Storage tanks and other

containers must be earthed.

## 7.2. Conditions for safe storage, including any incompatibilities

#### **QUALUBE SYNTOGEAR TDL 80W90**

Storage precautions The container choice, for example storage vessel, may effect static accumulation and

dissipation. Store in closed original container at temperatures between 5°C and 25°C.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description AVOID CONTACT WITH SKIN AND EYES.

# SECTION 8: Exposure Controls/personal protection

# 8.1. Control parameters

### Occupational exposure limits

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ mist Short-term exposure limit (15-minute): WEL 10 mg/m³ mist

WEL = Workplace Exposure Limit

#### 8.2. Exposure controls

## Protective equipment







**Eye/face protection** Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is

required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

protection

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Hygiene measures Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

When using do not eat, drink or smoke. Discard contaminated shoes and clothing.

**Respiratory protection** No special requirements under ordinary conditions of use and with adequate ventilation.

Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

**Environmental exposure** 

controls

Comply with applicable enivronmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit

emissions.

# **SECTION 9: Physical and Chemical Properties**

# 9.1. Information on basic physical and chemical properties

Appearance Viscous liquid.

Colour Brownish.

Odour Slight.

Flash point > 200°C PMCC (Pensky-Martens closed cup).

Vapour pressure <0.1 mm Hg @ 20°C

Solubility(ies) Insoluble in water.

**Viscosity** 13.5-18.5 cSt @ 100°C

#### **QUALUBE SYNTOGEAR TDL 80W90**

9.2. Other information

Other information DMSO Extract(mineral oil only), IP-346: < 3% wt.

# SECTION 10: Stability and reactivity

10.1. Reactivity

**Reactivity** See sub sections below.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Will not polymerise.

reactions

10.4. Conditions to avoid

**Conditions to avoid** Excessive heat. High energy sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

None at ambient temperatures.

products

#### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Aspiration hazard

Aspiration hazard Pneumonia may be the result if vomited material containing solvents reaches the lungs.

# **SECTION 12: Ecological Information**

12.1. Toxicity

**Toxicity** Material not expected to be harmful to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability Material- expected to be inherently biodegradable.

12.3. Bioaccumulative potential

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.

12.4. Mobility in soil

**Mobility** The product is insoluble in water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

# SECTION 13: Disposal considerations

# 13.1. Waste treatment methods

#### **QUALUBE SYNTOGEAR TDL 80W90**

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Empty containers must not be punctured or incinerated

because of the risk of an explosion.

Waste class European waste code: 13 02 05

# SECTION 14: Transport information

**General** The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

# 14.1. UN number

Not classified as dangerous goods for transport.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

Not applicable.

#### 14.4. Packing group

Not applicable.

## 14.5. Environmental hazards

# Environmentally hazardous substance/marine pollutant

No.

# 14.6. Special precautions for user

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not determined

Annex II of MARPOL 73/78

and the IBC Code

#### SECTION 15: Regulatory information

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

Health and Safety at Work etc. Act 1974 (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives

0.1/4.55/550 0.02/57/550 0.01/4.55/50 0.01/4.

91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

# 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

#### SECTION 16: Other information

# **QUALUBE SYNTOGEAR TDL 80W90**

**Issued by** Technical manager

Revision date 08/02/2016

SDS number 20573

Hazard statements in full H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H361 Suspected of damaging fertility or the unborn child. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.