

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ

AIRCO FLUSH
Material Safety Data Sheet
EU

Section 1 – Product and Company Information

Product Name: AIRCO BIOFLUSH
Product Codes: AC2141
Manufactured By: PRIMALEC
Unit 1 West Kingsdown Ind Estate, West Kingsdown, Kent TN15 6EL
Telephone: +44 (0)1474 854417
Emergency Telephone: +44 (0)1474 853968

Section 2 – Composition and Information on Ingredients

COMPONENTS	CAS NO.	PEL/TLV-SOURCE
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm TWA, 150 ppm STEL (OSHA, ACGIH)
Propylene Glycol Butyl Ether	5131-66-8	Not Established
Non-ionic detergent <1%		

All components of this product are listed on the U.S. TSCA inventory or are exempt from TSCA inventory requirements.

Section 3 – Hazard Identification

Carcinogenicity: Not listed for any component at 0.1% or greater
Primary Route(s) of Entry: Skin contact, absorption, eye contact, inhalation

Skin contact: Repeated exposure may cause skin irritation

Eye contact: May cause moderate eye irritation or corneal injury. Vapors may irritate eyes.

Inhalation: Brief inhalation exposure not likely to cause adverse effects. Higher levels may cause narcosis

Section 4 – First Aid Procedures

- | | |
|--------------|---|
| Skin Contact | • Thoroughly wash the exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. |
| Eye Contact | • Flush with large amounts of water, lifting upper and lower lids occasionally. Get medical attention. |
| Ingestion | • Immediately drink a large amount of water. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately. |
| Inhalation | • If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, quiet, and get medical attention. |

Section 5 – Fire Fighting Measures

Flash Point (Method Used): 71°C (160°F) (ASTM D-93) Extinguishing Media: Use alcohol foam, carbon dioxide or dry chemical extinguishing media

Special Fire Fighting Procedures: Wear self-contained Unusual Fire & Explosion Hazards: Avoid all sources of

breathing apparatus in the positive pressure demand mode when fighting fires

ignition – heat, sparks, open flame. Vapors are heavier than air.

Section 6– Accidental Release Measures

Steps to be taken in case material is released or spilled:

Small Spill or Large Spill: Spill should be contained and placed in suitable containers for disposal

Waste Disposal Method: Do not dispose to sewers, on the ground, or into any body of water. All disposal methods must be in compliance with local laws and regulations. Waste characterizations and compliance are the responsibility of the waste generator.

For unused and uncontaminated product, the preferred options include sending to a licensed, permitted recycler, reclaimer, incinerator or other thermal destruction device.

Section 7 – Handling and Storage

Respiratory Protection: If work place exposure limit(s) of product or any component is exceeded (see section 2), a Niosh/MSHA approved air supplied respirator is advised in absence of proper environmental control engineering, or administrative controls should be implemented to reduce exposure.

Ventilation: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(S).

Section 8 – Exposure Controls/Personal Protection

Eye Protection: Chemical splash goggles in compliance with OSHA regulations are advised. However, OSHA regulations also permit other type safety glasses (consult your safety equipment supplier).

Protective Gloves: Wear resistant gloves such as Neoprene.

Other Protective Equipment: To prevent repeated or prolonged skin contact, wear impervious clothing or boots.

Section 9 – Physical and Chemical Properties

Boiling Point: 171°C (340°F)

Specific Gravity (H₂O = 1): 0.91-0.92

% Volatile Organic Compounds: 99+

Freeze Point: <-73°C (<-100°F)

Vapor Density (Air=1): N/D

% Volatile (By Weight): 99+

Solubility of Water in Product: >100g/100g Product

Appearance / Odor: Clear colorless liquid, Slight Ether Odor

pH: Not Applicable, Non Aqueous

Section 10 – Stability and Reactivity

Stability: Stable

Hazardous Polymerization: Cannot Occur

Incompatibility: Avoid contact with strong oxidizing agents

Hazardous Decomposition or Byproducts: Under Fire Conditions: Fumes, smoke, carbon dioxide, carbon monoxide, and other decomposition products

Section 11 – Toxicological Information

See section 3 for health hazard information

Section 12 – Ecological Information

Propylene glycol butyl ether is readily biodegradeable and is practically non-toxic to aquatic organisms.
Dipropylene glycol methyl ether is not considered a hazardous waste.

Section 13 – Ecological Information

See section 6. Dispose of product according to local regulations

Section 14 – Transport Information

DOT (49 CFR 172): Not Regulated

Bill of Lading: Cleaning compound IT 48580 S3

Poison Constituent: None

Marine Pollutant: No

Section 15 – Transport Information

Label requirement: St. Andrew's cross with caption "irritating"

Warning Statements:

R36/37/38 – Irritating to eyes, respiratory system and skin

S2 – keep out of reach of children

S36/37/39 – wear suitable protective clothing, gloves and eye/face protection

S24/25 – avoid contact with skin and eyes

S46 – if swallowed, seek medical advice immediately and show this container or label.

Section 16 – Other Information

While Primalec believes the data set forth herein are accurate as of the date hereof, Primalec makes no warranty with respect thereto and expressly disclaims all liability for reliance thereon. Such data are offered solely for your consideration, investigation, and verification.

Date: 9 September, 2002