Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

(*) Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



Safety Data Sheet according to Regulation (EC) No 1907/2006

Page 1 of 20

Loctite 243 Threadlocker

SDS No. : 316211 V009.3 Revision: 21.12.2016 printing date: 10.04.2017 Replaces version from: 14.12.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Loctite 243 Threadlocker

Contains:

Tetramethylene dimethacrylate Maleic acid Acetic acid, 2-phenylhydrazide

1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use: Adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Wood Lane End HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 1442 278000 Fax-no.: +44 1442 278071

ua-productsafety.uk@uk.henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizerH317 May cause an allergic skin reaction.Chronic hazards to the aquatic environmentH411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Category 1

Category 2

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.
Precautionary statement:	***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of waste and residues in accordance with local authority requirements***
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General chemical description: Anaerobic adhesive

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No.	EC Number REACH-Reg No.	content	Classification
Tetramethylene dimethacrylate 2082-81-7	218-218-1 01-2119967415-30	25- 50 %	Skin Sens. 1B H317
2,4,6-Triallyloxy-s-triazine 101-37-1	202-936-7 01-2119489756-17	5- < 10 %	Acute Tox. 4; Oral H302 Aquatic Chronic 2 H411
2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy]methyl]-2- ethyl-1,3-propanediyl diacrylate 94108-97-1	302-434-9 01-2119977121-41	1-< 5%	Eye Irrit. 2 H319 Aquatic Chronic 2 H411
Fatty acid amide	484-050-2 01-0000020228-74	0,25-< 2,5 %	Aquatic Acute 1 H400 Aquatic Chronic 1 H410 M factor (Acute Aquat Tox): 10 M factor (Chron Aquat Tox): 10
Cumene hydroperoxide 80-15-9	201-254-7	0,1-< 1 %	Acute Tox. 4; Dermal H312 STOT RE 2 H373 Acute Tox. 4; Oral H302 Org. Perox. E H242 Acute Tox. 3; Inhalation H331 Aquatic Chronic 2 H411 Skin Corr. 1B H314
Acetic acid, 2-phenylhydrazide 114-83-0	204-055-3	0,1-< 1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3; Inhalation H335 Carc. 2 H351
Maleic acid 110-16-7	203-742-5 01-2119488705-25	0,1-< 1 %	Acute Tox. 4; Oral H302 Acute Tox. 4; Dermal H312 Skin Irrit. 2 H315 Skin Sens. 1 H317 Eye Irrit. 2 H319 STOT SE 3 H335
1,4-Naphthalenedione 130-15-4	204-977-6	0,01-< 0,1 %	Acute Tox. 3; Oral H301 Skin Irrit. 2; Dermal H315 Skin Sens. 1; Dermal H317 Eye Irrit. 2 H319 Acute Tox. 1; Inhalation H330 STOT SE 3; Inhalation H335

Aquatic Acute 1
H400
Aquatic Chronic 1
H410
M factor (Acute Aquat Tox): 10 M factor
(Chron Aquat Tox): 10

For full text of the H - statements and other abbreviations see section 16 "Other information". Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Rinse with running water and soap. Obtain medical attention if irritation persists.

Eye contact: Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion: Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: Carbon dioxide, foam, powder Fine water spray

Extinguishing media which must not be used for safety reasons: None known

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid skin and eye contact. Ensure adequate ventilation.

6.2. Environmental precautions

Do not let product enter drains.

6.3. Methods and material for containment and cleaning up

For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Use only in well-ventilated areas. Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation. Avoid skin and eye contact. See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed. Do not eat, drink or smoke while working. Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

7.3. Specific end use(s) Adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4 [DUST, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [DUST, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		EH40 WEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL VAPOUR AND PARTICULATES]	150	474	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for Ireland

Ingredient [Regulated substance]	ррт	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, RESPIRABLE]		4	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [DUSTS, NON-SPECIFIC, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, PARTICULATES]		10	Time Weighted Average (TWA):		IR_OEL
Propane-1,2-diol 57-55-6 [PROPANE-1,2-DIOL, TOTAL (VAPOUR AND PARTICULATES)]	150	470	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Value				Remarks	
		period	mg/l	ppm	mg/kg	others	
2,4,6-Triallyloxy-1,3,5-triazine	aqua		g/1	ppm	, ng	0,00705 mg/L	
101-37-1	(freshwater)					Ū.	
2,4,6-Triallyloxy-1,3,5-triazine	aqua (marine					0,0007 mg/L	
101-37-1	water)						
2,4,6-Triallyloxy-1,3,5-triazine	aqua					0,0705 mg/L	
101-37-1	(intermittent						
2.4.6 Tri-ll-l-m 1.2.5 tri-in-	releases)				0,1729		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sediment (freshwater)				0,1729 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine	sediment				0,01729		
101-37-1	(marine water)				mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine	soil				0.057		
101-37-1					mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine	sewage					10 mg/L	
101-37-1	treatment plant						
	(STP)						
2,4,6-Triallyloxy-1,3,5-triazine	oral				0,119		
101-37-1					mg/kg	0.0010 7	
2-[[2,2-Bis[[(1- oxoallyl)oxy]methyl]butoxy]methyl]-2-	aqua (freshwater)					0,0012 mg/L	
ethyl-1,3-propanediyl diacrylate	(freshwater)						
94108-97-1							
2-[[2,2-Bis[[(1-	soil				0,098		
oxoallyl)oxy]methyl]butoxy]methyl]-2-					mg/kg		
ethyl-1,3-propanediyl diacrylate					0.0		
94108-97-1							
2-[[2,2-Bis[[(1-	sediment				0,0493		
oxoallyl)oxy]methyl]butoxy]methyl]-2-	(marine water)				mg/kg		
ethyl-1,3-propanediyl diacrylate							
94108-97-1 2-[[2,2-Bis[[(1-	sediment				0,493		
oxoallyl)oxy]methyl]butoxy]methyl]-2-	(freshwater)				0,493 mg/kg		
ethyl-1,3-propanediyl diacrylate	(Inconvator)				iiig/ kg		
94108-97-1							
2-[[2,2-Bis[[(1-	sewage					100 mg/L	
oxoallyl)oxy]methyl]butoxy]methyl]-2-	treatment plant					_	
ethyl-1,3-propanediyl diacrylate	(STP)						
94108-97-1							
2-[[2,2-Bis[[(1-	aqua					0,012 mg/L	
oxoallyl)oxy]methyl]butoxy]methyl]-2- ethyl-1,3-propanediyl diacrylate	(intermittent releases)						
94108-97-1	releases)						
2-[[2,2-Bis[[(1-	aqua (marine					0,00012 mg/L	
oxoallyl)oxy]methyl]butoxy]methyl]-2-	water)					0,00012 mg/L	
ethyl-1,3-propanediyl diacrylate							
94108-97-1							
Fatty acid amide	aqua					0,000146	
	(freshwater)					mg/L	
Fatty acid amide	aqua (marine					0,0146 g/L	
P	water)					0.00025 4	
Fatty acid amide	aqua (intermittent					0,00025 mg/L	
	(interinitient releases)						
Fatty acid amide	sediment				5,554		
r any acto annue	(marine water)				mg/kg		
Fatty acid amide	aqua				55,54		
•	(freshwater)				mg/kg		
Fatty acid amide	soil				66,576		
					mg/kg		
Fatty acid amide	sewage					10 mg/L	
	treatment plant						
alaha alaha Dimethalka 1	(STP)					0.0021	
.alpha.,.alphaDimethylbenzyl hydroperoxide	aqua (freshwater)					0,0031 mg/L	
80-15-9	(inesitwater)						
	1		+			0,00031 mg/L	
.alphaalphaDimethylbenzyl	aqua (marine						
.alpha.,.alphaDimethylbenzyl hydroperoxide	aqua (marine water)					0,00031 llig/L	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	aqua (marine water)					0,00051 mg/L	
hydroperoxide						0,031 mg/L	

80-15-9	releases)	ĺ	1	
.alpha.,.alphaDimethylbenzyl	Sewage		0,35 mg/L	
hydroperoxide 80-15-9	treatment plant			
.alpha.,.alphaDimethylbenzyl	sediment	0,023		
hydroperoxide 80-15-9	(freshwater)	mg/kg		
.alpha.,.alphaDimethylbenzyl	sediment	0,0023		
hydroperoxide 80-15-9	(marine water)	mg/kg		
.alpha.,.alphaDimethylbenzyl	soil	0,0029		
hydroperoxide 80-15-9		mg/kg		
Maleic acid 110-16-7	aqua (freshwater)		0,1 mg/L	
Maleic acid	aqua		0,4281 mg/L	
110-16-7	(intermittent		0,4201 mg/L	
	releases)			
Maleic acid	sediment	0,334		
110-16-7	(freshwater)	mg/kg		
Maleic acid	sewage		44,6 mg/L	
110-16-7	treatment plant (STP)			
Maleic acid	aqua (marine		0,01 mg/L	
110-16-7	water)			
Maleic acid	sediment	0,0334		
110-16-7	(marine water)	mg/kg		
Maleic acid	soil	0,0415		
110-16-7		mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Tetramethylene dimethacrylate 2082-81-7	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg bw/day	
Tetramethylene dimethacrylate 2082-81-7	Workers	inhalation	Long term exposure - systemic effects		14,5 mg/m3	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Acute/short term exposure - systemic effects		134,4 mg/m3	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	dermal	Long term exposure - systemic effects		1,5 mg/kg bw/day	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Long term exposure - systemic effects		2,12 mg/m3	
2-[[2,2-Bis[[(1- oxoallyl)oxy]methyl]butoxy]methyl]-2- ethyl-1,3-propanediyl diacrylate 94108-97-1	Workers	Inhalation	Long term exposure - systemic effects		5,88 mg/m3	
2-[[2,2-Bis[[(1- oxoallyl)oxy]methyl]butoxy]methyl]-2- ethyl-1,3-propanediyl diacrylate 94108-97-1	Workers	dermal	Long term exposure - systemic effects		1,67 mg/kg bw/day	
Fatty acid amide	General population	oral	Long term exposure - systemic effects		8,3 mg/kg bw/day	
Fatty acid amide	General population	dermal	Long term exposure - systemic effects		8,3 mg/kg bw/day	
Fatty acid amide	Workers	dermal	Long term exposure - systemic effects		14 mg/kg bw/day	
Fatty acid amide	General population	inhalation	Long term exposure - systemic effects		2,9 mg/m3	
Fatty acid amide	Workers	inhalation	Long term exposure - systemic effects		9,8 mg/m3	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects		6 mg/m3	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - local effects		0,55 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - local effects		0,04 mg/cm2	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - systemic effects		58 mg/kg bw/day	
Maleic acid 110-16-7	Workers	dermal	Long term exposure - systemic effects		3,3 mg/kg bw/day	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - systemic effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Long term exposure - local effects		3 mg/m3	
Maleic acid 110-16-7	Workers	inhalation	Acute/short term exposure - systemic effects		3 mg/m3	

Biological Exposure Indices: None

8.2. Exposure controls:

Engineering controls: Ensure good ventilation/extraction.

Respiratory protection: Ensure adequate ventilation. An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection: Wear suitable protective clothing. Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	liquid blue
Odor	characteristic
Odour threshold	No data available / Not applicable
pH	No data available / Not applicable
Initial boiling point	>70 °C (>158 °F)
Flash point	> 110 °C (> 230 °F)
Decomposition temperature	No data available / Not applicable
Vapour pressure (25 °C (77 °F))	1,7 mbar
Vapour pressure (50 °C (122 °F))	< 300 mbar
Density ()	1,15 - 1,20 g/cm3
Bulk density	No data available / Not applicable
Viscosity	No data available / Not applicable
Viscosity (kinematic)	No data available / Not applicable

Explosive properties	No data available / Not applicable
Solubility (qualitative)	Insoluble
(Solvent: Water)	
Solubility (qualitative)	Soluble
(Solvent: Acetone)	
Solidification temperature	No data available / Not applicable
Melting point	No data available / Not applicable
Flammability	No data available / Not applicable
Auto-ignition temperature	No data available / Not applicable
Explosive limits	No data available / Not applicable
Partition coefficient: n-octanol/water	No data available / Not applicable
Evaporation rate	No data available / Not applicable
Vapor density	No data available / Not applicable
Oxidising properties	No data available / Not applicable

9.2. Other information

No data available / Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity Peroxides.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

Oral toxicity:

May cause irritation to the digestive tract.

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Prolonged or repeated contact may cause eye irritation.

Sensitizing:

May cause an allergic skin reaction.

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Tetramethylene	LD50	10.120 mg/kg	oral		rat	not specified
dimethacrylate						
2082-81-7						
2,4,6-Triallyloxy-s-	LD50	753 mg/kg	oral		rat	OECD Guideline 401 (Acute
triazine						Oral Toxicity)
101-37-1						
2-[[2,2-bis[[(1-	LD50	> 5.000 mg/kg	oral		rat	OECD Guideline 401 (Acute
oxoallyl)oxy]methyl]buto						Oral Toxicity)
xy]methyl]-2-ethyl-1,3-						
propanediyl diacrylate						
94108-97-1	1.0.50	2 000 1				
Fatty acid amide	LD50	> 2.000 mg/kg	oral		rat	not specified
Cumene hydroperoxide	LD50	550 mg/kg	oral		rat	not specified
80-15-9		0.0				
Maleic acid	LD50	708 mg/kg	oral		rat	not specified
110-16-7						
1,4-Naphthalenedione	LD50	190 mg/kg	oral		rat	not specified
130-15-4						

Acute inhalative toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
Hazar dous componentis	value	value	Route of	Exposure	opecies	Michiou
CAS-No	type		application	time		
CAS-NO.	type		application	time		

Acute dermal toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
2,4,6-Triallyloxy-s-	LD50	> 2.000 mg/kg	dermal		rabbit	OECD Guideline 402 (Acute
triazine						Dermal Toxicity)
101-37-1						
Fatty acid amide	LD50	> 2.000 mg/kg	dermal		rat	not specified
Cumene hydroperoxide 80-15-9	LD50	1.200 - 1.520 mg/kg	dermal			not specified
Maleic acid 110-16-7	LD50	1.560 mg/kg	dermal		rabbit	not specified

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Maleic acid 110-16-7	irritating	24 h	human	Patch Test

Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]buto xy]methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1	Category II		rabbit	EU Method B.5 (Acute Toxicity: Eye Irritation / Corrosion)
Maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Tetramethylene dimethacrylate 2082-81-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Maleic acid 110-16-7	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Maleic acid 110-16-7	sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Cumene hydroperoxide 80-15-9	negative	dermal		mouse	not specified
Maleic acid 110-16-7	negative	bacterial reverse mutation assay (e.g Ames test)	no data		Ames Test
	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity:

Hazardous components CAS-No.	Result	Species	Sex	Exposure timeFrequenc y of treatment	Route of application	Method
Maleic acid 110-16-7	not carcinogenic	rat	male/female	2 y daily	oral: feed	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

Hazardous substances CAS-No.	Result / Classification	Species	Exposure time	Species	Method
Maleic acid 110-16-7	NOAEL F1 = 150 mg/kg NOAEL F2 = 55 mg/kg	Two generation study oral: gavage	min. 80 d	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

Repeated dose toxicity

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d5 d/w	rat	not specified
Maleic acid 110-16-7	NOAEL=>= 40 mg/kg	oral: feed	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

General ecological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

12.1. Toxicity

Ecotoxicity:

Do not empty into drains / surface water / ground water. Toxic to aquatic life with long lasting effects.

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LC50	32,5 mg/l	Fish	48 h		DIN 38412-15
Tetramethylene dimethacrylate 2082-81-7	EC50	9,79 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2002-01-7	NOEC	2,11 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tetramethylene dimethacrylate 2082-81-7	NOEC	20 mg/l	Bacteria	28 d	activated sludge, domestic	not specified
Tetramethylene dimethacrylate 2082-81-7	NOEC	5,09 mg/l	chronic Daphnia	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test
2082-81-7 2,4,6-Triallyloxy-s-triazine 101-37-1	LC50	4,36 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,4,6-Triallyloxy-s-triazine 101-37-1	EC50	19,4 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
2,4,6-Triallyloxy-s-triazine 101-37-1	EC0	5 mg/l	Bacteria	3 h		Test) OECD Guideline 209 (Activated Sludge, Respiration
2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate	LC50	1,2 mg/l	Fish	96 h	Cyprinus carpio	Inhibition Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
94108-97-1 2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate	EC50	> 10 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
94108-97-1 2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1	EC50	> 12 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
94108-97-1	NOEC	< 0,35 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	201 (Alga, Growth
Fatty acid amide	NOEC	> 0,024 mg/l	Fish	96 h	Cyprinus carpio	Inhibition Test) OECD Guideline 203 (Fish, Acute
Fatty acid amide	NOEC	> 0,024 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Fatty acid amide	EC50	0,025 mg/l	Algae	72 h		Test) OECD Guideline 201 (Alga, Growt
	NOEC	0,0073 mg/l	Algae	72 h		Inhibition Test) OECD Guideline 201 (Alga, Growt
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	Fish	96 h	Oncorhynchus mykiss	Inhibition Test) OECD Guideline 203 (Fish, Acute
Cumene hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Cumene hydroperoxide 80-15-9	ErC50	3,1 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified
Maleic acid 110-16-7	LC50	> 245 mg/l	Fish	48 h	Leuciscus idus	DIN 38412-15
Maleic acid	EC50	42,81 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline

110-16-7						202 (Daphnia sp.
						Acute
						Immobilisation
						Test)
Maleic acid	EC50	74,35 mg/l	Algae	72 h	Pseudokirchnerella subcapitata	OECD Guideline
110-16-7		-	•		-	201 (Alga, Growth
						Inhibition Test)
1,4-Naphthalenedione	EC50	0,011 mg/l	Algae	72 h	Dunaliella bioculata	OECD Guideline
130-15-4		, i i i i i i i i i i i i i i i i i i i	•			201 (Alga, Growth
						Inhibition Test)

12.2. Persistence and degradability

Persistence and Biodegradability: The product is not biodegradable.

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
Tetramethylene dimethacrylate 2082-81-7	readily biodegradable	aerobic	84 %	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
2,4,6-Triallyloxy-s-triazine 101-37-1		aerobic	7 - 9 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1		aerobic	4 - 14 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Fatty acid amide		aerobic	7 %	not specified
Cumene hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
1,4-Naphthalenedione 130-15-4		no data	0 - 60 %	OECD 301 A - F

12.3. Bioaccumulative potential / 12.4. Mobility in soil

Mobility:

Cured adhesives are immobile.

Bioaccumulative potential: No data available.

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			

Tetramethylene dimethacrylate 2082-81-7 2,4,6-Triallyloxy-s-triazine	3,1			20 °C	OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method) not specified
101-37-1	_,~				
2-[[2,2-bis[[(1- oxoallyl)oxy]methyl]butoxy] methyl]-2-ethyl-1,3- propanediyl diacrylate 94108-97-1	4,14			30 °C	OECD Guideline 117 (Partition Coefficient (n- octanol / water), HPLC Method)
Cumene hydroperoxide 80-15-9 Cumene hydroperoxide 80-15-9	2,16	9,1	calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test) not specified
Acetic acid, 2- phenylhydrazide 114-83-0	0,74				not specified
Maleic acid 110-16-7	-1,3			20 °C	OECD Guideline 107 (Partition Coefficient (n- octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71				not specified

12.5. Results of PBT and vPvB assessment

Hazardous components	PBT/vPvB
CAS-No.	
Tetramethylene dimethacrylate	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
2082-81-7	Bioaccumulative (vPvB) criteria.
2,4,6-Triallyloxy-s-triazine	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
101-37-1	Bioaccumulative (vPvB) criteria.
2-[[2,2-bis[[(1-	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
oxoallyl)oxy]methyl]butoxy]methyl]-2-ethyl-	Bioaccumulative (vPvB) criteria.
1,3-propanediyl diacrylate	
94108-97-1	
Cumene hydroperoxide	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
80-15-9	Bioaccumulative (vPvB) criteria.
Maleic acid	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
110-16-7	Bioaccumulative (vPvB) criteria.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Dispose of in accordance with local and national regulations. Contribution of this product to waste is very insignificant in comparison to article in which it is used

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

Waste code

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

DR ID DN MDG ATA N proper ship DR ID	3082 3082 3082 3082 3082 3082 ping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid		
ID DN MDG ATA 'N proper ship DR ID	3082 3082 3082 3082 pping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
.DN MDG ATA 'N proper ship .DR ID	3082 3082 3082 ping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
MDG ATA I N proper ship .DR ID	3082 3082 ping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
ATA I <mark>N proper ship</mark> .DR .ID	3082 ping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
' N proper ship .DR .ID	ping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
.DR ID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
ID	amide)		
DN	amide)		
	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
MDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Fatty acid amide)		
ATA	Environmentally hazardous substance, liquid, n.o.s. (Fatty acid amide)		
Transport hazard class(es)			
DR	9		
	9		
	9		
	9		
ATA	9		
acking group			
DR	III		
ID	III		
.DN	III		
MDG	III		
ATA	III		
nvironmontol	hazanda		
aivii oiiinciitai	nazai us		
.DR	not applicable		
ID	not applicable		
.DN	not applicable		
MDG	Marine pollutant		
АТА	not applicable		
Special precautions for user			
DR	not applicable		
	Tunnelcode: (E)		
ID	not applicable		
.DN	not applicable		
MDG	not applicable		
ATA	not applicable		
ontainers with a g for solid subs	assifications in this section apply generally to packed and bulk goods alike. For a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 stances per individual or inner package, the exemptions SP 375 (ADR), 197 (IATA), y be applied, which can result in a deviation from the transport classification for packed		
	ATA ransport haza DR ID DN MDG ATA acking group DR ID DN MDG ATA nvironmental DR ID DN MDG ATA pecial precaut DR ID DN MDG ATA he transport cla ontainers with a g for solid subs 59 (IMDG) ma		

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC content (2010/75/EC) < 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

- H301 Toxic if swallowed. H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H331 Toxic if inhaled.
- H335 May cause respiratory irritation. H351 Suspected of causing cancer.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Label elements (DPD):

Xi - Irritant

N - Dangerous for the environment



Risk phrases:

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases:

- S24 Avoid contact with skin.
- S37 Wear suitable gloves.
- S61 Avoid release to the environment. Refer to special instructions/Safety data sheets.

Additional labeling:

For consumer use only: S2 Keep out of the reach of children.

S46 If swallowed, seek medical advice immediately and show this container or label.

Contains:

Maleic acid, Tetramethylene dimethacrylate

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.