Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ





材料安全数据表 Material Safety Data Sheet

货 物 名 称: 锂离子可充电电芯

Name of Goods: Lithium ion Rechargeable Cell

委 托 单 位: 深圳市东恒新能源科技有限公司

Commissioner: Shenzhen Dongheng New Energy

Technology Co., Ltd

广东联鼎检测科技有限公司 GUANGDONG UTL CO., LTD.

Report No.: 17PNS12039 01021

材料安全数据表 Material Safety Data Sheet

1. Identification of the product and supplier (产品和厂商信息)			
样品名称 Name of goods	锂离子可充电电芯 Lithium ion Rechargeable Cell		
样品型号 Type/Mode	INR18650P, 3.7V 2000mAh 7.4Wh		
委托单位 Commissioned by	深圳市东恒新能源科技有限公司 Shenzhen Dongheng New Energy Technology Co., Ltd		
委托单位地址 Commissioner address	深圳市坪山新区坪山办事处石井社区草埔村竹青路1号 Zhuqing Road No.1, Caopu Village, Shijing Community Pingshan Office, Pingshan New District, Shenzhen City, Guangdong Province, China		
制造商 Manufacturer	深圳市东恒新能源科技有限公司 Shenzhen Dongheng New Energy Technology Co., Ltd		
制造商地址 Manufacturer address	深圳市坪山新区坪山办事处石井社区草埔村竹青路1号 Zhuqing Road No.1, Caopu Village, Shijing Community Pingshan Office, Pingshan New District, Shenzhen City, Guangdong Province, China		
生产厂 Factory	深圳市东恒新能源科技有限公司 Shenzhen Dongheng New Energy Technology Co., Ltd		
生产厂地址 Factory address	深圳市坪山新区坪山办事处石井社区草埔村竹青路1号 Zhuqing Road No.1, Caopu Village, Shijing Community Pingshan Office, Pingshan New District, Shenzhen City, Guangdong Province, China		
鉴定依据 Inspection according to	EEC Directive 93/112/EC 联合国《关于危险品货物运输的建议书》 UN "Recommendations on the TRANSPORT OF DANGEROUS GOODS"		
紧急联系电话 Emergency telephone call	+86-755-84620699		
接样日期 / Receiving date: 2017-12-15		签发日期 / Issue date: 2018-01-03	

Reviewed by:

审核 灵顺文

Tested by:

TAN PAS

Page 3 of 8 Report No.: 17PNS12039 01021

2. Composition/Information on Ingredient (成分/组成信息)			
危险成分(化学名称) Hazardous Ingredients (Chemical Name)	含量及含量百分比(%) Concentration or concentration ranges (%)	CAS编号 CAS Number	
钴酸锂/ Lithium Cobalt Oxide	30-40	346417-97-8	
聚偏氟乙烯/ Polyvinylidene Fluoride(PVDF)	1-2	24937-79-9	
石墨/ Graphite	11-18	7782-42-5	
丁苯橡胶/ Styrene-Butadiene Rubber (SBR)	1-3	9003-55-8	
羧甲基纤维素/ Carboxymethylcellulose	1-2	9000-11-7	
铝/ Aluminium(Al)	4-6	7429-90-5	
铜/ Copper (Cu)	3-7	7440-50-8	
镍/ Nickel (Ni)	3-5	7440-02-0	
六氟磷酸锂/ Lithium Hexafluorophosphate	12-17	21324-40-3	
聚丙烯/ Polypropylene	0.05-0.1	9003-07-0	
其他/ Others	1-2		

3. Hazards Identification (主要危险性鉴定)		
爆炸危险性 Explosive risk	该物品不属于爆炸危险品 This article does not belong to the explosion dangerous goods	
易燃危险性	该物品不属于易燃危险品	
Flammable risk	This article does not belong to the flammable material	
氧化危险性	该物品不属于氧化危险品	
Oxidation risk	This article does not belong to the oxidation of dangerous goods	
毒害危险性	该物品不属于毒害危险品	
Toxic risk	This article does not belong to the toxic dangerous goods	
放射危险性	该物品不属于放射危险品	
Radioactive risk	This article does not belong to the radiation of dangerous goods	
腐蚀危险性	该物品不属于腐蚀危险品	
Mordant risk	This article does not belong to the corrosion of dangerous goods	
其他危险性	该物品为锂离子可充电电芯,瓦时率为7.4Wh	
other risk	This article is the Lithium ion Rechargeable Cell, Watt hour rate 7.4Wh	

Page 4 of 8 Report No.: 17PNS12039 01021

4. First aid measures (急救措施)

Eye

Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.

Skin

Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.

Inhalation

Remove from exposure and move to fresh air immediately. Use oxygen if available.

Ingestion

Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.

5. Fire-fighting measures (消防措施)

Flash Point: N/A.

Auto-Ignition Temperature: N/A.
Extinguishing Media: Water, CO2.
Special Fire-Fighting Procedures
Self-contained breathing apparatus.

Unusual Fire and Explosion Hazards

Cell may vent when subjected to excessive heat-exposing battery contents.

Hazardous Combustion Products

Carbon monoxide, carbon dioxide, lithium oxide fumes.

6. Accidental release measures (泄漏应急处理)

Steps to be Taken in case Material is Released or Spilled

If the battery material is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. Wipe it up with a cloth, and dispose of it in a plastic bag and put into a steel can. The preferred response is to leave the area and allow the battery to cool and vapors to dissipate. Provide maximum ventilation. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

Waste Disposal Method

It is recommended to discharge the battery to the end, to use up the metal lithium inside the battery, and to bury the discharged battery in soil.

GUANGDONG UTL CO., LTD.

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng Disctrict, Dongguan, Guangdong, China

Page 5 of 8 Report No.: 17PNS12039 01021

7. Handling and storage (操作处置和储存)

The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container.

Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire.

Do not crush or puncture the battery, or immerse in liquids.

Precautions to be taken in handling and storing

Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.

Other Precautions

The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection (接触控制/个人保护)

Respiratory Protection

In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.

Ventilation

Not necessary under conditions of normal use.

Other Protective Clothing or Equipment

Not necessary under conditions of normal use.

Personal Protection is recommended for venting battery

Respiratory Protection, Protective Gloves, Protective Clothing and safety glass with side shields.

9. Physical and chemical properties (物理和化学特性)

Appearance: Cylindrical shape **Ref. No.:** 17PNS12039 01001

Odour: If leaking, smells of medical ether.

pH: Not applicable as supplied.

Flash Point: Not applicable unless individual components exposed.
Flammability: Not applicable unless individual components exposed.
Relative density: Not applicable unless individual components exposed.
Solubility (water): Not applicable unless individual components exposed.
Solubility (other): Not applicable unless individual components exposed.

GUANGDONG UTL CO., LTD.

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng Disctrict, Dongguan, Guangdong, China

Page 6 of 8 Report No.: 17PNS12039 01021

10. Stability and reactivity (稳定性和反应活性)

Stability: Product is stable under conditions described in Section 7.

Conditions to avoid: Heat above 70°C or incinerate. Deform. Mutilate. Crush. Disassemble. Overcharge.

Short circuit. Expose over a long period to humid conditions.

Materials to avoid: Oxidising agents, alkalis, water.

Hazardous Decomposition Products: Toxic Fumes, and may form peroxides.

Hazardous Polymerization: N/A.

If leaked, forbidden to contact with strong oxidizers, mineral acids, strong alkalies, halogenated hydrocarbons.

11. Toxicological information (毒理性资料)

Signs & symptoms: None, unless battery ruptures.

In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.

Inhalation: Lung irritant.

Skin contact: Skin irritant

Eye contact: Eye irritant

Ingestion: Poisoning if swallowed

Medical conditions generally aggravated by exposure: In the event of exposure to internal contents, moderate to server irritation, burning and dryness of the skin may occur, Target organs nerves, liver and kidneys.

12. Ecological information (生态学资料)

Mammalian effects: None known at present.

Eco-toxicity: None known at present.

Bioaccumulation potential: Slowly Bio-degradable.

Environmental fate: None known environmental hazards at present.

13. Disposal consideration (废弃处置)

Do not incinerate, or subject cells to temperature in excess of 70°C, Such abuse can result in loss of seal leakage, and/or cell explosion. Dispose of in accordance with appropriate local regulations.

14. Transport information (运输信息)

Label for conveyance: Lithium Battery Label.

GUANGDONG UTL CO., LTD.

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng Disctrict, Dongguan, Guangdong, China

Page 7 of 8 Report No.: 17PNS12039 01021

UN Number: UN3480 Packing Group: N/A EmS No: F-A, S-I Marine pollutant: No

Proper Shipping name: Lithium ion batteries. (including Lithium ion polymer batteries)

Hazard Classification: The goods shall be complied with the requirements of Section IB of Packing Instructions 965 of 59th DGR Manual of IATA (2018 edition), including the passing of the UN38.3 test. And also complies with the Special Provision 188 of IMDG CODE (Amdt.37-14) 2014 Edition.

15. Regulation information (法规信息)

Law information

《Dangerous Goods Regulations》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《Resource Conservation and Recovery Act》 (RCRA)

《Safety Drinking Water Act》 (CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In accordance with all Federal, State and local laws.

16. Other information (其他信息)

This information is not effective to all the batteries manufactured by Shenzhen Dongheng New Energy Technology Co., Ltd .This information comes from reliable sources, but no warranty is made to the completeness and accuracy of information contained. GUANGDONG UTL CO., LTD. doesn't assume responsibility for any damage or loss because of misuse of batteries. User's should grasp the correct use method and be responsible for the use of batteries.

GUANGDONG UTL CO., LTD.

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng Disctrict, Dongguan, Guangdong, China

Page 8 of 8 Report No.: 17PNS12039 01021

Photos



Fig.1 Overall view I of cell



Fig.2 Overall view II of cell

Lianding Testing Building, No.18 Center Road of Yayuan Industrial Zone, Nancheng Disctrict, Dongguan, Guangdong, China