

Contact Sheet



Europe

 **Austria**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Belgium / Lux**
Tel: + 32 58235140
Sparex Belgium Bvba
Toevluchtweg 9
B- 8620 Nieuwpoort

 **Denmark**
Tel: + 45 647 22287
Sparex Denmark
Sparex Limited ApS
Messevej 1
9600 Aars

 **France**
Tel: +33 2987 89234
Sparex S.A.R.L.
Zae De Ty Douar
Commana 29450

 **Germany**
Tel: + 49 4282 93100
Sparex Germany
Hansestrasse 03
Sittensen 27419

 **Ireland**
Tel: +353 51 855592
Sparex (Tractor Accessories) Ltd
Grannagh
Waterford
Ireland

 **Italy**
Tel: + 43 4212 6400
Sparex Austria
Muraunberger Str
Hurzendorf 9300

 **Netherlands**
Tel: + 31 235 841 020
Sparex Holland BV
Luzernstraat 19N
2153 GM Nieuw-Vennep

 **Poland**
Tel: +48 61 816 19 37
61-168 ul. Rataje 164, Poznań

 **Portugal**
Tel: +351 261 311107
Sparex Portugal, Importação
e Comércio de Peças,Lda.
Lugar da Espera 2565-716 Runa.

 **Spain**
Tel: + 349 451 33524
Sparex Agrirepuestos,S.L. C/Jose Maria
Iparraguirre
No.15 B
01006 Vitoria-Gasteiz (Alava)

 **UK**
Tel: +44 1392 441338
Sparex Limited
Exeter Airport Devon
Exeter EX5 2LJ

North America

 **Canada**
Tel: + 905 786 277
Sparex Canada Highway
No. 2 On Newcastle L1b 119

 **USA**
Tel: + 1 330 562 8150
Sparex US
PO Box 510
Aurora, OH 44202

Africa

 **South Africa**
Cape - Tel: +27 00 21 887 3575
KZN - Tel: + 27 31 573 1240
Cape branch
35 George Blake St,
Plankenburg
Stellenbosch 7600
KZN branch
59 Marseilles crescent
Briardene
Durban 4001

Australasia

 **Australia**
Tel: + 61 298 205 777
Sparex Australia Pty Ltd
81-83 Strzelecki Avenue,
Sunshine West, VIC 3020

 **New Zealand**
Tel: + 64 9634 4121
4 Princes Street Onehunga,
Auckland 1345

Sparex Export Markets

 **Export**
Tel: +44 1392 441314
Sparex Limited
Exeter Airport
Devon Exeter EX5 2LJ

BONDLOCTM

FORMULAS THAT WORK

SAFETY DATA SHEET

B7772 Adhesive Spray

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name B7772 Adhesive Spray

Container size 400ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier

Bondloc UK Ltd
Unit 2 Bewdley Business Park
Long Bank
Bewdley
Worcestershire
DY12 2TZ
+44 (0)1299 269269
+44 (0)1299 269210
sales@bondloc.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1299 269269

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)


Physical hazards Aerosol 1 - H222, H229

Health hazards Carc. 2 - H351

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.
H229 Pressurised container: may burst if heated
H351 Suspected of causing cancer.
H412 Harmful to aquatic life with long lasting effects.

B7772 Adhesive Spray

Precautionary statements	<p>P201 Obtain special instructions before use.</p> <p>P202 Do not handle until all safety precautions have been read and understood.</p> <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P211 Do not spray on an open flame or other ignition source.</p> <p>P251 Do not pierce or burn, even after use.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P308+P313 IF exposed or concerned: Get medical advice/ attention.</p> <p>P405 Store locked up.</p> <p>P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	---

Contains dichloromethane

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

dichloromethane	30-60%
CAS number: 75-09-2	EC number: 200-838-9

Classification

Carc. 2 - H351

butane	10-30%
CAS number: 106-97-8	EC number: 203-448-7

Classification

Flam. Gas 1 - H220

n-hexane	1-5%
CAS number: 110-54-3	EC number: 203-777-6

Classification

Flam. Liq. 2 - H225

Skin Irrit. 2 - H315

Repr. 2 - H361f

STOT SE 3 - H336

STOT RE 2 - H373

Asp. Tox. 1 - H304

Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Move affected person to fresh air at once.

Inhalation Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention.

B7772 Adhesive Spray

Ingestion	Move affected person to fresh air at once. Rinse mouth. Do not induce vomiting. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	Treat symptomatically.
Inhalation	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems Prolonged inhalation of high concentrations may damage respiratory system. Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
Ingestion	Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
Skin contact	Product has a defatting effect on skin. Prolonged skin contact may cause redness and irritation.
Eye contact	Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Show this Safety Data Sheet to the medical personnel.
-----------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide or dry powder. Water spray, fog or mist.
-------------------------------------	---

5.2. Special hazards arising from the substance or mixture

Specific hazards	Pressurised container: may burst if heated
Hazardous combustion products	Toxic gases or vapours. Oxides of carbon.

5.3. Advice for firefighters

Protective actions during firefighting	Use water spray to reduce vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Avoid inhalation of vapours and contact with skin and eyes.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Eliminate all sources of ignition. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage.
--------------------------------	---

B7772 Adhesive Spray

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. Do not spray on an open flame or other ignition source. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a well-ventilated place. Keep away from heat, sparks and open flame. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Storage class Extremely flammable aerosol.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

dichloromethane

Long-term exposure limit (8-hour TWA): WEL 100 ppm 350 mg/m³

Short-term exposure limit (15-minute): WEL 300 ppm 1060 mg/m³

Sk

butane

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation.

Personal protection

Wear protective clothing.

Eye/face protection

Wear chemical splash goggles.

Hand protection

No specific hand protection recommended.

Other skin and body protection

Provide eyewash station.

Hygiene measures

When using do not eat, drink or smoke. Wash promptly if skin becomes contaminated.

Respiratory protection

Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. In case of possible exposure to degradation products, use suitable respiratory protection.

B7772 Adhesive Spray

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Amber.
Odour	Chlorinated hydrocarbons. Characteristic.
Odour threshold	Lower 100 ppm Upper 280 ppm
pH	Not available.
Melting point	Not available.
Initial boiling point and range	40°C @ 760 mm Hg
Flash point	-40°C CC (Closed cup).
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.8 Upper flammable/explosive limit: 9.5
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	log Pow: 1.25
Auto-ignition temperature	410°C
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Other information None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Stable under the prescribed storage conditions.

10.2. Chemical stability

Stability Highly volatile

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None known.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

B7772 Adhesive Spray

Materials to avoid Aluminium.

10.6. Hazardous decomposition products

Hazardous decomposition products In combustion emits toxic fumes

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Vapours may irritate throat/respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. High exposures may cause an abnormal heart rhythm and prove suddenly fatal. Vapours in high concentrations are anaesthetic.
Ingestion	Similar symptoms to inhalation
Skin contact	Harmful: danger of serious damage to health by prolonged exposure in contact with skin.
Eye contact	Irritation of eyes and mucous membranes.
Route of entry	Inhalation Skin and/or eye contact
Target organs	Central nervous system Respiratory system, lungs Liver

SECTION 12: Ecological Information

Ecotoxicity The product contains a substance which is very toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment. Do not discharge into drains or watercourses or onto the ground.

12.1. Toxicity

Ecotoxicity

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient log Pow: 1.25

12.4. Mobility in soil

Mobility No information available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Do not puncture or incinerate, even when empty. Empty containers must not be punctured or incinerated because of the risk of an explosion.

B7772 Adhesive Spray

Waste class Full or Partially Empty Aerosol: 16 05 04. Empty Aerosol: 15 01 10 (Containing hazardous residues). Empty Aerosol; 15 01 04 (No hazardous Residues).

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

ADR/RID class	2, 5f class 2:Gases
IMDG class	2.1
ICAO class/division	2.1

Transport labels



14.4. Packing group

ADR/RID packing group	#
IMDG packing group	#
ICAO packing group	#

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS	F-D, S-U
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

B7772 Adhesive Spray

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the council of 18 December 2006 concerning the Registration, evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labeling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	23/06/2015
SDS number	5054
Hazard statements in full	<p>H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H361f Suspected of damaging fertility. H373 May cause damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.</p>

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

WARRANTY: All products purchased from or supplied by Bondloc are subject to terms and conditions set out in the contract. Bondloc warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by Bondloc is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. Bondloc makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.