

# Contact Sheet



## Europe

 **Austria**  
Tel: + 43 4212 6400  
Sparex Austria  
Muraunberger Str  
Hurzendorf 9300

 **Belgium / Lux**  
Tel: + 32 58235140  
Sparex Belgium Bvba  
Toevluchtweg 9  
B- 8620 Nieuwpoort

 **Denmark**  
Tel: + 45 647 22287  
Sparex Denmark  
Sparex Limited ApS  
Messevej 1  
9600 Aars

 **France**  
Tel: +33 2987 89234  
Sparex S.A.R.L.  
Zae De Ty Douar  
Commana 29450

 **Germany**  
Tel: + 49 4282 93100  
Sparex Germany  
Hansestrasse 03  
Sittensen 27419

 **Ireland**  
Tel: +353 51 855592  
Sparex (Tractor Accessories) Ltd  
Grannagh  
Waterford  
Ireland

 **Italy**  
Tel: + 43 4212 6400  
Sparex Austria  
Muraunberger Str  
Hurzendorf 9300

 **Netherlands**  
Tel: + 31 235 841 020  
Sparex Holland BV  
Luzernstraat 19N  
2153 GM Nieuw-Vennep

 **Poland**  
Tel: +48 61 816 19 37  
61-168 ul. Rataje 164, Poznań

 **Portugal**  
Tel: +351 261 311107  
Sparex Portugal, Importação  
e Comércio de Peças,Lda.  
Lugar da Espera 2565-716 Runa.

 **Spain**  
Tel: + 349 451 33524  
Sparex Agrirepuestos,S.L. C/Jose Maria  
Iparraguirre  
No.15 B  
01006 Vitoria-Gasteiz (Alava)

 **UK**  
Tel: +44 1392 441338  
Sparex Limited  
Exeter Airport Devon  
Exeter EX5 2LJ

## North America

 **Canada**  
Tel: + 905 786 277  
Sparex Canada Highway  
No. 2 On Newcastle L1b 119

 **USA**  
Tel: + 1 330 562 8150  
Sparex US  
PO Box 510  
Aurora, OH 44202

## Africa

 **South Africa**  
Cape - Tel: +27 00 21 887 3575  
KZN - Tel: + 27 31 573 1240  
Cape branch  
35 George Blake St,  
Plankenburg  
Stellenbosch 7600  
KZN branch  
59 Marseilles crescent  
Briardene  
Durban 4001

## Australasia

 **Australia**  
Tel: + 61 298 205 777  
Sparex Australia Pty Ltd  
81-83 Strzelecki Avenue,  
Sunshine West, VIC 3020

 **New Zealand**  
Tel: + 64 9634 4121  
4 Princes Street Onehunga,  
Auckland 1345

## Sparex Export Markets

 **Export**  
Tel: +44 1392 441314  
Sparex Limited  
Exeter Airport  
Devon Exeter EX5 2LJ

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 1 of 10

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

TIP TOP CEMENT INNERLINER SEALER

###### Art.-No.

511 1190, 514 3240, 514 3250, 514 9301, 514 9302, 515 9004, 515 9005, 515 9011, 515 9012, 515 9027, 515 9028, 515 9029, 515 9035, 515 9042, 515 9058, 515 9059

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

###### Use of the substance/mixture

adhesive

##### 1.3. Details of the supplier of the safety data sheet

Company name: REMA TIP TOP AG

Street: Gruber Strasse 65

Place: D-85586 Poing

Telephone: +49 (0) 8121 / 707 - 100

Responsible Department: Responsible for the safety data sheet: sds@gbk-ingelheim.de

##### 1.4. Emergency telephone

###### number:

INTERNATIONAL: +49 - (0) 6132 - 84463, GBK GmbH (24h - 7d/w - 365d/a)

In England and Wales: NHS 111 In Scotland: NHS 24 - dial 111

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

##### 2.2. Label elements

###### Regulation (EC) No. 1272/2008

###### Hazard components for labelling

Naphtha (petroleum)

Signal word: Danger

###### Pictograms:



###### Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

###### Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
------	--



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 2 of 10

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P273	Avoid release to the environment.

#### 2.3. Other hazards

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

Vapours may form explosive mixture with air.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Chemical characterization

Preparation solved in petroleum spirit

##### Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane]	< 50 %		
	921-024-6		01-2119475514-35	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
64742-49-0	Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, < 5% n-hexane]	< 20 %		
	931-254-9		01-2119484651-34	
	Flam. Liq. 2, Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H315 H336 H304 H411			
1314-13-2	Zinc oxide	< 1 %		
	215-222-5	030-013-00-7	01-2119463881-32	
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			

Full text of H and EUH statements: see section 16.

##### Further Information

According to note P to the regulation (EC) no. 1272/2008, "Naphtha (petroleum)" is not to be classified as "carcinogenic" or "mutagen" ingredient because a benzene content (EINECS No. 200-753-7) is below 0.1 % by weight.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

Remove contaminated soaked clothing immediately.  
In the event of persistent symptoms receive medical treatment.  
Take away from danger area and lay down affected person.

##### After inhalation

Move to fresh air in case of accidental inhalation of vapours.  
Seek medical treatment immediately.

##### After contact with skin

Wash off with soap and plenty of water.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 3 of 10

Treat subsequently with skin cream.  
Consult a doctor if skin irritation persists.

#### **After contact with eyes**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Summon a doctor immediately.

#### **After ingestion**

Do not induce vomiting.  
Summon a doctor immediately.  
Induce vomiting only upon the advice of a physician.  
Attention. Beware, danger of aspiration.

#### **4.2. Most important symptoms and effects, both acute and delayed**

Causes skin irritation.  
May cause drowsiness or dizziness.  
Attention. Beware, danger of aspiration.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Alcohol-resistant foam, dry chemical, carbon dioxide (CO<sub>2</sub>), water-spray.

##### **Unsuitable extinguishing media**

Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

Fire may produce:  
Carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and sulphur oxides (SO<sub>x</sub>)

#### **5.3. Advice for firefighters**

Use breathing apparatus with independent air supply.  
Protective suit.

#### **Additional information**

Vapours are heavier than air and spread along ground.  
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.  
Cool containers at risk with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

In case of vapour formation use respirator.  
Avoid contact with skin, eyes and clothing.  
Ensure adequate ventilation.  
Remove persons to safety.  
Use personal protective clothing.  
Keep away sources of ignition.

#### **6.2. Environmental precautions**

Do not discharge into the drains/surface waters/ground water.

#### **6.3. Methods and material for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).  
Shovel into suitable container for disposal.

#### **6.4. Reference to other sections**

Observe protective instructions (see Sections 7 and 8).



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 4 of 10

Information for disposal see section 13.

#### SECTION 7: Handling and storage

##### 7.1. Precautions for safe handling

###### Advice on safe handling

- Keep container tightly closed.
- Vapours are heavier than air and spread along ground.
- Use only in thoroughly ventilated areas.

###### Advice on protection against fire and explosion

- Keep away from heat and sources of ignition.
- Do not smoke.
- Take precautionary measures against static discharges.
- Use only explosion-proof equipment.

##### 7.2. Conditions for safe storage, including any incompatibilities

###### Requirements for storage rooms and vessels

- Keep container tightly closed in a dry, cool and well-ventilated place.
- Pay attention to anti-explosion rules.

###### Advice on storage compatibility

- Incompatible with oxidizing agents.

###### Further information on storage conditions

- Keep away from food, drink and animal feeding stuffs.

##### 7.3. Specific end use(s)

adhesive

#### SECTION 8: Exposure controls/personal protection

##### 8.1. Control parameters

###### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1333-86-4	Carbon black	-	3.5		TWA (8 h)	WEL
		-	7		STEL (15 min)	WEL

##### 8.2. Exposure controls

###### Appropriate engineering controls

- Ensure adequate ventilation, especially in confined areas.

###### Protective and hygiene measures

- Do not inhale vapours.
- Wash hands before breaks and immediately after handling the product.
- When using do not eat, drink or smoke.
- Treat subsequently with skin cream.
- Avoid contact with skin, eyes and clothing.
- Remove and wash contaminated clothes before re-use.

###### Eye/face protection

- Tightly fitting goggles (EN 166).

###### Hand protection

- Protective gloves resistant to chemicals made off nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 5 of 10

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

#### Skin protection

Solvent-resistant apron (EN 467).

#### Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Black
Odour:	Hydrocarbon-like

#### Test method

pH-Value:	n.d.
-----------	------

#### Changes in the physical state

Melting point:	n.d.
Initial boiling point and boiling range:	60 - 95 °C
Sublimation point:	n.a.
Softening point:	n.d.
Flash point:	- 24 °C DIN EN ISO 3679

#### Flammability

Solid:	n.a.
Gas:	n.a.

#### Explosive properties

The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated.

Lower explosion limits:	1,0 vol. % *)
Upper explosion limits:	7,3 vol. % *)
Ignition temperature:	413 °C

#### Auto-ignition temperature

Solid:	n.a.
Gas:	n.a.

Decomposition temperature:	n.d.
----------------------------	------

#### Oxidizing properties

Not oxidising.

Vapour pressure: (at 20 °C)	150 hPa *)
--------------------------------	------------

Density:	0,83 g/cm <sup>3</sup>
----------	------------------------

Bulk density:	n.a.
---------------	------

Water solubility: (at 20 °C)	Immiscible
---------------------------------	------------

#### Solubility in other solvents

n.d.

Partition coefficient:	n.d.
------------------------	------

Viscosity / dynamic:	6000 mPa·s
----------------------	------------

Viscosity / kinematic: (at 40 °C)	> 20,5 mm <sup>2</sup> /s
--------------------------------------	---------------------------

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 6 of 10

Flow time:	n.d.
Vapour density:	n.d.
Evaporation rate:	7,6 *)
Solvent separation test:	0 %
Solvent content:	60 - 70 %

#### **9.2. Other information**

\*) Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane, Hydrocarbons, C6, isoalkanes, < 5% n-hexane

### **SECTION 10: Stability and reactivity**

#### **10.1. Reactivity**

No decomposition if stored and applied as directed.

#### **10.2. Chemical stability**

Stable under normal conditions.

#### **10.3. Possibility of hazardous reactions**

Reactions with oxidizing agents.

#### **10.4. Conditions to avoid**

To avoid thermal decomposition, do not overheat.  
Vapour/air mixtures are explosive at intensive warming.  
Heating can release vapours which can be ignited.

#### **10.5. Incompatible materials**

oxidizing agents

#### **10.6. Hazardous decomposition products**

Carbon monoxide, carbon dioxide, sulphur oxides.

### **SECTION 11: Toxicological information**

#### **11.1. Information on toxicological effects**

##### **Acute toxicity**

Based on available data, the classification criteria are not met.  
No toxicological data available.  
Naphtha (petroleum)  
LD50/oral/rat: > 2000 mg/kg  
LD50/dermal/rabbit: > 2000 mg/kg  
LC50/inhalation/rat: > 20 mg/l

##### **Irritation and corrosivity**

Causes skin irritation.  
Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

##### **Sensitising effects**

Based on available data, the classification criteria are not met.

##### **Carcinogenic/mutagenic/toxic effects for reproduction**

Based on available data, the classification criteria are not met.

##### **STOT-single exposure**

May cause drowsiness or dizziness. (Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, < 5% n-hexane])

##### **STOT-repeated exposure**

Based on available data, the classification criteria are not met.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 7 of 10

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

#### Practical experience

#### Other observations

Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Contact with eyes may cause irritation.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecological data are not available.

Naphtha (petroleum)

EC50/Daphnia: 1 - 10 mg/l

EC50/Algae: 10 - 100 mg/l

Zinc oxide

EC50/Ceriodaphnia dubia/48 h = 0,01 - 0,1 mg/l

EC50/Selenastrum capricornutum/72 h = 0,01 - 0,1 mg/l

Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

No data available

#### 12.3. Bioaccumulative potential

No data available

#### 12.4. Mobility in soil

No data available

#### 12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

#### 12.6. Other adverse effects

Low hazard to waters.

#### Further information

Do not flush into surface water or sanitary sewer system.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Can be incinerated, when in compliance with local regulations.

Where possible recycling is preferred to disposal.

##### Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU of adhesives and sealants (including waterproofing products); waste adhesives and sealants containing organic solvents or other hazardous substances; hazardous waste

##### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 8 of 10

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

Packaging that cannot be cleaned should be disposed of like the product.

#### SECTION 14: Transport information

##### Land transport (ADR/RID)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

##### Other applicable information (land transport)

HAZCHEM: 3YE

##### Inland waterways transport (ADN)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Classification code:	F1
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2

##### Marine transport (IMDG)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives (Naphtha (petroleum))
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Marine pollutant:	Yes
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
EmS:	F-E, S-D

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 9 of 10

#### Air transport (ICAO-TI/IATA-DGR)

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3



Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

#### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



#### 14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

#### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 28: Naphtha (petroleum) [Hydrocarbons, C6-C7, n-alkanes, iso-alkanes, cyclic compounds, &lt; 5% n-hexane]

Entry 29: Naphtha (petroleum) [Hydrocarbons, C6, isoalkanes, &lt; 5% n-hexane]

2004/42/EC (VOC): &lt; 70 %

Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

##### National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### 15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

### SECTION 16: Other information



## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### TIP TOP CEMENT INNERLINER SEALER

Revision date: 13.07.2018

Product code: 00156-0074

Page 10 of 10

#### Abbreviations and acronyms

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route  
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses  
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure  
IMDG = International Maritime Code for Dangerous Goods  
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization  
MARPOL = International Convention for the Prevention of Pollution from Ships  
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals  
CAS = Chemical Abstract Service  
EN = European norm  
ISO = International Organization for Standardization  
DIN = Deutsche Industrie Norm  
PBT = Persistent Bioaccumulative and Toxic  
vPvB = Very Persistent and very Bio-accumulative  
LD = Lethal dose  
LC = Lethal concentration  
EC = Effect concentration  
IC = Median immobilisation concentration or median inhibitory concentration

#### Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

#### Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*