Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 **Sparex Germany** Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



SAFETY DATA SHEET Bradex Easy Start

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Bradex Easy Start

Product number BES1A

Internal identification PA013L

REACH registration notesThis is a MIXTURE; no registration information contained in this document. Holts are classed

as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier A Holts Car Care Product

Holt Lloyd International Ltd

Barton Dock Road

Stretford Manchester

M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854

www.holtsauto.com

Contact person Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358

9167

National emergency telephone http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-

number helpdesks

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Acute Tox. 4 - H302 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or Xn;R22. F+;R12. R19,R52/53,R66,R67.

1999/45/EC)

2.2. Label elements

Pictogram





Signal word Danger

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/ container in accordance with local regulations.

Supplemental label

information

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH019 May form explosive peroxides.

Contains DIETHYL ETHER, Naphtha (petroleum), hydrotreated light, DI-ISOPROPYL ETHER,

ACETONE

Supplementary precautionary

statements

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P301+P312 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P330 Rinse mouth.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

DIETHYL ETHER 10-30%

CAS number: 60-29-7 EC number: 200-467-2

Classification (67/548/EEC or 1999/45/EC)

Flam. Lig. 1 - H224 F+;R12 R19 Xn;R22 R66 R67

Acute Tox. 4 - H302 STOT SE 3 - H336 Revision date: 06/09/2016 Revision: 6 Supersedes date: 08/09/2014

Bradex Easy Start

Naphtha (petroleum), hydrotreated light 10-30%

CAS number: 64742-49-0 EC number: 265-151-9

 Classification
 Classification (67/548/EEC or 1999/45/EC)

 Flam. Liq. 2 - H225
 Xn;R65. Xi;R38. F;R11. N;R51/53. R67.

Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411

DI-ISOPROPYL ETHER 10-30%

CAS number: 108-20-3 EC number: 203-560-6

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Lig. 2 - H225 F;R11 R19 R66 R67

STOT SE 3 - H336

BUTANE 10-30%

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+;R12

Press. Gas

ACETONE 5-10%

CAS number: 67-64-1 EC number: 200-662-2

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Liq. 2 - H225 F;R11 Xi;R36 R66 R67

Eye Irrit. 2 - H319 STOT SE 3 - H336

ISOBUTANE 5-10%

CAS number: 75-28-5 EC number: 200-857-2

Classification Classification (67/548/EEC or 1999/45/EC)

Flam. Gas 1 - H220 F+:R12

Press. Gas

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Keep affected person warm and at rest. Get

medical attention immediately.

Ingestion DO NOT induce vomiting. Get medical attention immediately.

Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Revision date: 06/09/2016 Revision: 6 Supersedes date: 08/09/2014

Bradex Easy Start

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure. Get medical attention promptly if symptoms occur after washing.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea. In case of overexposure,

organic solvents may depress the central nervous system causing dizziness and intoxication,

and at very high concentrations unconsciousness and death.

Ingestion Due to the physical nature of this material it is unlikely that swallowing will occur.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

Pain.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

5.3. Advice for firefighters

Protective actions during

exposed containers cool and disperse vapours.

firefighting

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Not considered to be a significant hazard due to the small quantities used.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Leave small quantities to evaporate, if safe to do so. Do not allow material to enter confined spaces, due to the risk of

Containers close to fire should be removed or cooled with water. Use water to keep fire

explosion. If leakage cannot be stopped, evacuate area.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and

eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air

contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

DIETHYL ETHER

Long-term exposure limit (8-hour TWA): WEL 100 ppm 310 mg/m³ Short-term exposure limit (15-minute): WEL 200 ppm 620 mg/m³

DI-ISOPROPYL ETHER

Long-term exposure limit (8-hour TWA): WEL 250 ppm 1060 mg/m³ Short-term exposure limit (15-minute): WEL 310 ppm 1310 mg/m³

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³ Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours and spray/mists. Observe any occupational exposure limits for the product or ingredients.

No specific eye protection noted, but may be required anyway. Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible.

Other skin and body

Eye/face protection

protection

Wear appropriate clothing to prevent reasonably probable skin contact.

Hygiene measures Wash hands after handling.

Respiratory protection No specific recommendations.

Environmental exposure

controls

Residues and empty containers should be taken care of as hazardous waste according to

local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Clear liquid. Colourless.

Odour Organic solvents.

-38°C Flash point 180°C

9.2. Other information

Auto-ignition temperature

Other information Not relevant.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Vapours may form explosive mixtures with air.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:

Strong oxidising agents. Strong alkalis. Strong mineral acids.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

Other health effects There is no evidence that the product can cause cancer.

Acute toxicity - oral

ATE oral (mg/kg) 1,857.36

Inhalation Vapours may cause drowsiness and dizziness. Vapours may cause headache, fatigue,

dizziness and nausea.

Ingestion Harmful if swallowed. Swallowing concentrated chemical may cause severe internal injury.

Skin contact Irritating to skin. Product has a defatting effect on skin. May cause allergic contact eczema.

Eye contact Vapour or spray in the eyes may cause irritation and smarting. Repeated exposure may cause

chronic eye irritation.

Route of entry Inhalation Skin and/or eye contact

SECTION 12: Ecological Information

Ecotoxicity Dangerous for the environment. May cause long-term adverse effects in the aquatic

environment. However, The product is not expected to be toxic to aquatic organisms.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is expected to be biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potentialThe product does not contain any substances expected to be bioaccumulating.

12.4. Mobility in soil

Mobility The product contains volatile organic compounds (VOCs) which will evaporate easily from all

surfaces.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects The product contains volatile organic compounds (VOCs) which have a photochemical ozone

creation potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Empty containers must not be punctured or incinerated because of the risk of an explosion.

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or

watercourses.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

ADR/RID packing group None

IMDG packing group None

ADN packing group None

ICAO packing group None

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Authorisations (Title VII

Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII

No specific restrictions on use are known for this product.

Regulation 1907/2006)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 06/09/2016

Revision 6

Supersedes date 08/09/2014

SDS number 14771

Risk phrases in full R11 Highly flammable.

R12 Extremely flammable.

R19 May form explosive peroxides.

R22 Harmful if swallowed. R36 Irritating to eyes. R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H224 Extremely flammable liquid and vapour. H225 Highly flammable liquid and vapour. H229 Pressurised container: may burst if heated

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.