Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

(*) Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com

Page 1/9



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Revision: 22.08.2017

· 1.1 Product identifier · Trade name: EXO 27 MULTIGREASE PTFE 500 ML • Article number: TD81410 · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available. · Sector of Use SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC24 Lubricants, greases, release products · Process category **PROC7** Industrial spraying PROC11 Non industrial spraying · Environmental release category ERC8a Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8d Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor) · Application of the substance / the mixture Lubricant \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Tegee-dan Helge Nielsens Allé 7 1A 8723 Løsning DENMARK T: +45 7563 1370 F: +45 75631371 www.tegee-dan.dk info@tegee-dan.dk · Further information obtainable from: Department Product Safety · 1.4 Emergency telephone number: +45 7563 1370 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. Aerosol 1 GHS09 environment Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. GHS07 STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. (Contd. on page 2) GB Page 2/9


Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

Trade name: EXO 27 MULTIGREASE PTFE 500 ML



• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

25 .500/
25-<50%
12.5-<20%
10-<12.5%

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

		(Contd. of page 2)
CAS: 75-28-5	isobutane	10-<12.5%
EINECS: 200-857-2	🚯 Flam. Gas 1, H220	-
Index number: 601-004-00-0	Press. Gas C, H280	
Reg.nr.: 01-2119485395-27		
EC number: 920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	10-<12.5%
Index number: 649-328-00-1	🚸 Flam. Liq. 2, H225	-
Reg.nr.: 01-2119473851-33	🚯 Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	🔥 STOT SE 3, H336	
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
 Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:
- Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

(Contd. of page 3)

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

• Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:
- Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
- Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to: Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB -

Page 5/9

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

(Contd. of page 4)

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

• Eye protection: Not required.

1 Information on kasis sharis at a	a minute antica
9.1 Information on basic physical and ch General Information	iemicai properties
Appearance:	
Form:	Aerosol
Colour:	Whitish
Odour:	Solvent-like
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.
Flash point:	<0°C (<32 °F)
	Not applicable, as aerosol.
Flammability (solid, gas):	Not applicable.
Ignition temperature:	285°C (545 °F)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20°C (68 °F):	8,300 hPa (6,225 mm Hg)
Density at 20°C (68 °F):	0.67 g/cm ³ (5.591 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	63.4 %
EU-VOC:	497.3 g/l
EU-VOC in %:	74.00 %
VOC (EC)	 407.2 c/l
VOC-EU%	497.3 g/l 74.00 %
Solids content:	0.0 %

(Contd. on page 6)

Page 6/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

(Contd. of page 5)

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*
- · STOT-single exposure
- May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Page 7/9

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

(Contd. of page 6)

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

· European waste catalogue

20 01 13* solvents

15 01 04 metallic packaging

· Uncleaned packaging:

• Recommendation: Non contaminated packagings may be recycled.

14.1 UN-Number	
ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
IMDG	AEROSOLS (PENTANES, Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG	
Class Label	2.1 2.1
	2.1
IATA	
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	not regulated
14.5 Environmental hazards:	
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler): EMS Number:	- F-D,S-U

Page 8/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

	(Contd. of page
 Stowage Code Segregation Code 	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre. Category A. For AEROSOLS with a capacity above 1 litre. Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
• 14.7 Transport in bulk according to Annex Marpol and the IBC Code	II of Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity Code: E0 Not permitted as Excepted Quantity
· Transport category	2
• Tunnel restriction code	D
· <i>IMDG</i>	
· Limited quantities (LQ)	1L
$\cdot Excepted$ quantities (\widetilde{EQ})	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category
- P3a FLAMMABLE AEROSOLS
- E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.

(Contd. on page 9)

⁻ GB

Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 22.08.2017

Version number 154

Revision: 22.08.2017

Trade name: EXO 27 MULTIGREASE PTFE 500 ML

	(Contd. of page
H30	4 May be fatal if swallowed and enters airways.
	6 May cause drowsiness or dizziness.
	1 Toxic to aquatic life with long lasting effects.
	reviations and acronyms:
	Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the
	ational Transport of Dangerous Goods by Rail)
	D: International Civil Aviation Organisation
ADR:	: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International
	iage of Dangerous Goods by Road)
	G: International Maritime Code for Dangerous Goods
IATA	: International Air Transport Association
GHS:	: Globally Harmonised System of Classification and Labelling of Chemicals
EINE	CCS: European Inventory of Existing Commercial Chemical Substances
ELIN	ICS: European List of Notified Chemical Substances
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
VOC:	: Volatile Organic Compounds (USA, EU)
PBT:	Persistent, Bioaccumulative and Toxic
vPvB	: very Persistent and very Bioaccumulative
	. Gas 1: Flammable gases – Category 1
Aeros	sol 1: Aerosols – Category 1
	s. Gas C: Gases under pressure – Compressed gas
	. Liq. 1: Flammable liquids – Category 1
	. Liq. 2: Flammable liquids – Category 2
	FSE 3: Specific target organ toxicity (single exposure) – Category 3
	Tox. 1: Aspiration hazard – Category 1
	tic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
* Da	ata compared to the previous version altered.