Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



SAFETY DATA SHEET QUALUBE LITHIUM EP0 GREASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name QUALUBE LITHIUM EP0 GREASE

Product number EP0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Grease.

1.3. Details of the supplier of the safety data sheet

Supplier WITHAM OIL AND PAINT LTD

OUTER CIRCLE ROAD

LINCOLN LN2 4HL 01522 521192 01522 537030 01522 560228

enquires@withamgroup.co.uk

1.4. Emergency telephone number

Emergency telephone (01522) 521192 Monday to Thursday 8.00am to 5.00pm, Friday 8.00am to 4.30pm.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

Classification (67/548/EEC or -

1999/45/EC)

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

No significant hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

QUALUBE LITHIUM EPO GREASE

NON CLASSIFIED COMPONENT

60-100%

CAS number: -

Classification Classification (67/548/EEC or 1999/45/EC)

Not Classified -

Phosphorodithioic acid, mixed 0,0-bis(2-ethylhexyl and iso-

<1%

bu and iso-pr) esters, zinc salts

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Chronic 2 - H411

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments H350 does not apply. IP346 DMSO Extract <3%. Mixture of severely hydrogenated solvent

neutral oils and additives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination.

Inhalation Remove affected person from source of contamination.

Ingestion Get medical attention. Do not induce vomiting.

Skin contact Wash skin thoroughly with soap and water. If product is injected into or under the skin, or into

any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment

within the first few hours may significantly reduce the ultimate extent of injury.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

General information No ill effects.

Skin contact Prolonged contact may cause redness, irritation and dry skin.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Eye Contact: immediately washout with plenty of water.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media

5.2. Special hazards arising from the substance or mixture

Specific hazards In case of fire, toxic and corrosive gases may be formed.

QUALUBE LITHIUM EPO GREASE

Hazardous combustion

products

Fire creates: Thermal decomposition or combustion products may include the following substances: Acrid smoke or fumes. Aldehydes, Sulphur oxides, Incomplete combustion

products, Carbon monoxide (CO). Carbon dioxide (CO2).

5.3. Advice for firefighters

Protective actions during

firefighting

Evacuate area. Control run-off water by containing and keeping it out of sewers and

watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Transfer to a container for disposal.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling, skin and eye contact.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in closed original container at temperatures between 5°C and 25°C.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

Usage description AVOID CONTACT WITH SKIN AND EYES.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³ mist Short-term exposure limit (15-minute): WEL 10 mg/m³ mist

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment







QUALUBE LITHIUM EPO GREASE

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible.

Hand protection Wear protective gloves made of the following material: Polyvinyl chloride (PVC).

Other skin and body

protection

No skin protection is ordinarily required under normal conditions of use. In accordance with

good industrial hygiene practices, precautions should be taken to avoid skin contact.

Hygiene measures Remove contaminated clothing and wash the skin thoroughly with soap and water after work.

When using do not eat, drink or smoke. Discard contaminated shoes and clothing.

Respiratory protectionNo special requirements under ordinary conditions of use and with adequate ventilation.

Environmental exposure

controls

Comply with applicable enivronmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit

emissions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Grease.

Colour Brown.

Odourless.

Melting point >185°C

Flash point > 200°C PMCC (Pensky-Martens closed cup).

Vapour pressure <0.1 mm Hg @ 20°C

Relative density 0.82-0.85

Solubility(ies) Insoluble in water.

Auto-ignition temperature >200°C

9.2. Other information

Other information DMSO Extract(mineral oil only), IP-346: < 3% wt.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

None known.

reactions

10.4. Conditions to avoid

Conditions to avoid Excessive heat.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

QUALUBE LITHIUM EPO GREASE

Hazardous decomposition

products

None at ambient temperatures.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Not irritating.

Respiratory sensitisation

Respiratory sensitisation There is evidence that the product can cause respiratory hypersensitivity.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro No evidence

Carcinogenicity

Carcinogenicity There is no evidence that the product can cause cancer.

Reproductive toxicity

Reproductive toxicity - fertility This substance has no evidence of toxicity to reproduction.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

Toxicity Material not expected to be harmful to aquatic organisms.

12.2. Persistence and degradability

Persistence and degradability The product is expected to be slowly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential Product is not expected to bio-accumulate.

12.4. Mobility in soil

Mobility It the product enters soil, it will adsorb to soil particles and will not be mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site

in accordance with the requirements of the local Waste Disposal Authority.

QUALUBE LITHIUM EPO GREASE

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Empty containers must not be punctured or incinerated

because of the risk of an explosion.

Waste class European waste code: 13 02 05

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not classified as dangerous goods for transport.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not determined

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

Health and Safety at Work etc. Act 1974 (as amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives

91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Issued by Technical manager

QUALUBE LITHIUM EPO GREASE

Revision date 18/02/2016

SDS number 20585

Hazard statements in full H315 Causes skin irritation.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.