Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com

Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SAFETY DATA SHEET

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY NAME 1

NAME OF MANUFACTURER/SUPPLIER:

Witham Oil & Paint Ltd Outer Circle Road Lincoln LN2 4HL

01522 521192 / 537030
01522 560228
01522 537030
enquiries@withamgroup.co.uk
Mon to Thursday 7:00 – 17:00, Friday 7:00 – 16:30

PRODUCT NAME:

QUALUBE QUALGUARD HYBRID COOLANT

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Repr 1B	H360FD	May damage fertility. May damage the unborn child
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure
Acute Tox. 4	H302	Harmful if swallowed
Classification according to Directive 67/548/EEC or Directive 1999/45/EC		
т	Tavia	

I	IOXIC
R60-61	May impair fertility. May cause harm to the unborn child
Xn	Harmful
R22	Harmful if swallowed

Information concerning particular hazards for human and environment

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version

Classification system

The classification is according to the latest editions of the EU-lists, and extended by company and literature data

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation

Hazard pictograms 1 GHS07 GHS08

(ancil/hybridcoolant131014)

(Issue 1 MAK)

(1 of 10)

Manufacturers of Quality Lubricants & Paints since 1921

THE WITHAM GROUP



WITHAM OIL & PAINT (SOHAM) LTD 28 Regal Drive Soham Cambs CB7 5BE T. 01353 723373 F. 01353 624533

HEAD OFFICE WITHAM OIL & PAINT LTD Outer Circle Road Lincoln LN2 4HL T. 01522 521192/537030 F. 01522 560228

WITHAM OIL & PAINT (LOWESTOFT) LTD Stanley Road Oulton Broad Lowestoft Suffolk NR33 9ND T. 01502 563434 F. 01502 500010 Email. enquiries@withamgroup.co.uk www.withamgroup.co.uk



Signal word

Danger Hazard-determining components of labelling

Ethanediol Disodium tetraborate pentahydrate Sodium nitrite

Hazard statements

mazaru statem	
H302	Harmful if swallowed
H360FD	May damage fertility. May damage the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
Precautionary	statements
P260	Do not breathe dust/fume/gas/mist/vapours/spray
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P264	Wash possible exposed body surfaces thoroughly after handling this product
P405	Store locked up
P501	Dispose of contents/container in accordance with local/regional/national/international regulations
2 3 Other haz	ards

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable**vPvB:**Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Chemical characterization: Substances

Identification numbers Not applicable

3.2 Chemical characterization: Mixtures

Description

Dangerous Components:		
CAS: 107-21-1 EINECS: 203-473-3 Reg nr: 01-2119456816-28	ethanediol Xn R22 STOT RE2, H373; O Acute Tox, 4, H302	50-100%
CAS: 12179-04-3 EINECS: 215-540-4 Reg nr: 01-2119490790-32	disodium tetraborate pentahydrate T Repr Cat 1 R60-61: Xi R36 Repr 1B, H360FD; C Eye Irrit 2, H319	0.1-<1%
CAS: 7632-00-0 EINECS: 231-555-9 Reg nr: 01-2119471836-27	sodium nitrate T R25; O R8; N R50 Ox.Sol.2, H272; Acute Tox.3, H301; Aquatic acute 1, H400; Eye Irrit.2, H319	0.1-<1%
SVHC		
12179-04-03	disodium tetraborate pentahydrate	

Additional Information

For the wording of the listed risk phrases refer to section 16

4. FIRST AID MEASURES

4.1 Description of first aid measures

General information

Immediately remove any clothing soiled by the product After inhalation Supply fresh air or oxygen; call a doctor In case of unconsciousness place patient stably in side position for transportation After skin contact Immediately wash with water and soap and rinse thoroughly If skin irritation continues, consult a doctor After eye contact Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor After swallowing Do not induce vomiting; call for medical help immediately Rinse out mouth and then drink plenty of water

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions Water haze Alcohol resistant foam CO2 Fire-extinguishing powder BC Powder Sand

5.2 Special hazards arising from the substance or mixture

No further relevant information available

5.3 Advice for firefighters

Protective equipment Wear self-contained respiratory protective device **Additional information** Cool endangered receptacles with water spray

(ancil/hybridcoolant 131014)

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources Wear protective clothing Ensure adequate ventilation

6.2 Environmental precautions

Do not allow to enter sewers/surface or ground water Inform respective authorities in case of seepage into water course or sewage system

6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust) Dispose contaminated material as waste according to item 13

6.4 Reference to other sections

See Section 7 for information on safe handling See Section 8 for information on personal protection equipment See Section 13 for disposal information

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Keep receptacles tightly sealed Ensure good ventilation/exhaustion at the workplace

Information about fire - and explosion protection

Keep ignition sources away - Do not smoke Protect against electrostatic charges

7.2 Conditions for safe storage, including any incompatibilities Storage

Requirements to be met by storerooms and receptacles No special requirements

Information about storage in one common storage facility

Do not store together with acids Store away from flammable substances Store away from water

Further information about storage conditions

Store in cool, dry conditions in well-sealed receptacles Store receptacle in fume cupboard

7.3 Specific end use(s)

No further relevant information available

(ancil/hybridcoolant 131014)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Addition information about design of technical facilities:

No further data: see item 7

8.1 Control Parameters

8.1 Control Parameters				
	Ingredients with limit values that require monitoring at the workplace:			
107-21-1 ethanediol				
WEL		Short-term value: 104**mg/m³, 40**ppm		
	Long-term value: 10* 52**mg/m ³ , 20**ppm			
	Sk * particulate **vapour			
DNELS				
107-21-1 ethanediol				
Dermal	DNEL Long-term – Systemic (consumer)	53mg/kg bw/day(/)		
	DNEL Long-term – Systemic (worker)	106 mg/kg bw/day (/)		
Inhalative	DNEL Long-term – Local (consumer)	$7 mg/m^{3}(/)$		
	DNEL Long-term – Local (worker)	35mg/m ³ (/)		
12179-04-3 disodium tetraborate	e pentahydrate			
Oral	DNEL Acute – Systemic (consumer)	1.15mg/kg bw/day (/)		
	DNEL Long-term – Systemic (consumer)	1.15mg/kg bw/day (/)		
Dermal	DNEL Long-term – Systemic (consumer)	231.8mg/kg bw/day (/)		
	DNEL Long-term – Systemic (worker)	458.2mg/kg bw/day (/)		
Inhalative	DNEL Acute – Local (consumer)	17.04 mg/m ³ (/)		
	DNEL Acute – Local (worker)	17.04 mg/m ³ (/)		
	DNEL Long-term – Local (consumer)	17.04 mg/m ³ (/)		
	DNEL Long-term – Local (worker)	17.04 mg/m ³ (/)		
	DNEL Long-term – Systemic (consumer)	4.9 mg/m^{3} (/)		
	DNEL Long-term – Systemic (worker)	9.8mg/m ³ (/)		
7632-00-0 sodium nitrite		5.5mg/m (//		
Inhalative	DNEL Acute – Systemic (worker)	2mg/m ³ (/)		
innalative	DNEL Long-term – Systemic (worker)	$2mg/m^{3}(/)$		
PNECs		2		
107-21-1 ethanediol				
PNEC Fresh water	10mg/l (/)			
PNEC Marine water	1 mg/l (/)			
PNEC Soil	1.53mg/kg (/)			
12179-04-3 disodium tetraborato PNEC Fresh water				
	2.02mg/l (/)			
PNEC Intermittent releases	13.7 mg/l (/)			
PNEC Marine water	2.02 mg/l(/)			
PNEC STP	10mg/l (/)			
PNEC Soil 5.4 mg/kg (/)				
7632-00-0 sodium nitrite				
PNEC Fresh water	0.0054 mg/l (/)			
PNEC Fresh water sediment	0.0195 mg/kg (/)			
PNEC Intermittent releases	0.0054 mg/l (/)			
PNEC Marine sediment	0.0223 mg/kg (/)			
PNEC Marine water		0.00616 mg/l (/)		
PNEC STP				
PNEC Soil	0.000733 mg/kg (/)			

Additional Information

The lists valid during the making were used as basis

8.2 Exposure controls Personal protective equipment

General protective and hygienic measures The usual precautionary measures are to be adhered to when handling chemicals Keep away from foodstuffs, beverages and feed Wash hands before breaks and at the end of work

Respiratory protection

Not required

Protection of hands



Protective gloves

The glove material has to be impermeable and resistant to the product/the substance/the preparation. Due to missing tests, no recommendation to the glove material can be given for the product/the preparation/the chemical mixture

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be check prior to the application

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed

Eye Protection

Tightly sealed goggles

Body Protection

Use protective suit

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Fluid	
Colour:	Blue / Blue in UK	
Odour:	Odourless	
Odour Threshold:	Not determined	
pH value:	Not determined	
Change in condition		
Melting point/Melting range:	Undetermined	
Boiling point/Boiling range:	197°C	
Flash point:	111°C	
Auto ignition temperature:	398°C	
Decomposition temperature:	Not determined	
Self-igniting:	Product is not self-igniting	

(ancil/hybridcoolant 131014)

Danger of explosion: Exposure limits	Product does not present an explosion hazard
Lower:	3.2 vol %
Upper:	53 vol %
Vapour pressure:	Not determined
Density at 20°C:	1.11g/cm ³
Relative density:	Not determined
Vapour density:	Not determined
Evaporation rate:	Not determined
Solubility in/Miscibility with	
Water at 20°C:	1 g/l
Partition coefficient	-
(n-octanol/water):	Not determined
Viscosity	
Dynamic:	Not determined
Kinematic:	Not determined
Solvent content	
Organic solvents:	0.0%

9.2 Other information

No further relevant information available

10. STABILITY AND REACTIVITY

10.1 Reactivity

10.2 Chemical stability Thermal decomposition/conditions to be avoided No decomposition if used according to specifications 10.3 Possibility of hazardous reaction No dangerous reactions known 10.4 Conditions to avoid No further relevant information available 10.5 Incompatible materials Acids Strong oxidizing agents 10.6 Hazardous decomposition products No dangerous decomposition products known

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects Acute toxicity:

LD/LC50 values relevant for classification:		
107-21-1 ethanediol		
Oral	LD50	>300-<2000 mg/kg (rat)
Dermal	LD50	>5000mg/kg (rabbit)

(ancil/hybridcoolant 131014)

(Issue 1 MAK)

(7 of 10)

12179-04-3 disodium tetraborate pentahydrate		
Oral	LD50	3200-3400mg/kg (rat)
Dermal	LD50	>2000mg/kg (rabbit)
Inhalative	LC50	>2.0mg/l (rat)
7632-00-0 sodium nitrite		
Oral	LD50	180 mg/kg (rat)

Primary irritant effect:

on the skin No irritant effect

on the eye No irritating effect

Sensitization No sensitizing effects known

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Harmful

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Repr 1B

12. ECOLOGICAL INFORMATION

12.1 Toxicity

Aquatic toxicity		
107-21-1 ethanediol		
EC 50 (48 u)	> 100mg/l (daphnia magna)	
EC 50 (96 u)	6500-13000 mg/l (pseudokirchneriella subcapitata)	
LC 50 (96 u)	72860 mg/l (pimephales promelas)	
12179-04-3 disodium tetrab	porate pentahydrate	
EC 50 (24 u)	242mg/l (daphnia magna)	
LC 50	88mg/l (oncorhynchus mykiss) (24 days)	
	65mg/l (carassius auratus) (7 days)	
7632-00-0 sodium nitrite		
EC 50 (48 u)	421 mg/l (Protozoa)	
15.4 mg/l (daphnia magna) (OECD 202)		
LC 50 (48 u)	360 mg/l (Leuciscus idus)	
LC 50 (96 u)	0.54-26.3 mg/l (Oncorhynchus mykiss)	
NOEC	9.86 mg/l (daphnia)	
	6.16 mg/l (Ictalarus punctatus)	

12.2 Persistence and degradability

No further relevant information available

12.3 Bioaccumulative potential

No further relevant information available

12.4 Mobility in soil

No further relevant information available

Additional ecological information

General Notes

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(ancil/hybridcoolant 131014)

(Issue 1 MAK)

(8 of 10)

12.5 Results of PBT and vPvB assessment

PBT: Not applicable **vPvB:** Not applicable 12.6 Other adverse effects No further relevant information available

13. DISPOSAL RECOMMENDATIONS

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system Uncleaned packaging recommendation Disposal much be made according to official regulations

14. TRANSPORT INFORMATION

14.1 UN-Number	
ADR, ADN, IMDG, IATA	Void
14.2 UN proper shipping name	
ADR, ADN, IMDG, IATA	Void
14.3 Transport Hazard Class(es)	
ADR, ADN, IMDG, IATA	
Class	Void
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards	
Marine Pollutant	No
14.6 Special precautions for user	Not applicable
14.7 Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable
UN "Model Regulation"	-

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Labelling according to Regulation (EC) No 1272/2008 GHS label elements

National regulations Technical instructions (air)

Class	Share in %
NK	95.0

Water hazard class

Water hazard class 1 (Self assessment); slightly hazardous for water **15.2 Chemical safety assessment** A Chemical Safety Assessment has not been carried out

16. OTHER INFORMATION

The information provided in these documents is based on our present state of knowledge of the product and is given in good faith and to the best of our experience. However, it should not be construed as a technical specification or as guaranteeing specific properties. In no event we will be responsible for damages or effects of any nature whatsoever, either express or implied, resulting from the use of this information. It is the own responsibility of the consignee and the user of the product to comply with all prevailing and applicable laws, regulations and directives. They should also make their own determination as to the suitability of the product for a particular use of application

Relevant phrases

Relevant p	phrases	
H272	May intensify fire; oxidizer	
H301	Toxic if swallowed	
H302	Harmful if swallowed	
H319	Causes serious eye irritation	
H360FD	May damage fertility, May damage the unborn child	
H373	May cause damage to organs through prolonged or repeated exposure	
H400	Very toxic to aquatic life	
R22	Harmful if swallowed	
R25	Toxic if swallowed	
R36	Irritating to eyes	
R50	Very toxic to aquatic organisms	
R60	May impair fertility	
R61	May cause harm to the unborn child	
R8	Contact with combustible material may cause fire	
	ions and acronyms	
	national Civil Aviation Organisation	
	ean Agreement concerning the International Carriage of Dangerous Goods by Road	
	rnational Maritime Code for Dangerous Goods	
	national Air Transport Association	
GHS: Globally Harmonized System of Classification and Labelling of Chemicals		
	ropean inventory of Existing Commercial Chemical Substances	
	ropean List of Notified Chemical Substances	
	ical Abstracts Service (division of the American Chemical Society)	
	ved No-Effect Level (REACH)	
	icted No-Effect Concentration (REACH)	
	l concentration, 50 percent	
	al dose, 50 percent	
	ent, Bioaccumulative and Toxic	
	stances of Very High Concern	
	Persistent and very Bioaccumulative	
	xidising Solids, Hazard Category 2	
	Acute toxicity, Hazard Category 3	
Acute Tox 4: Acute toxicity, Hazard Category 4		
Eye Irrit 2: S	Eye Irrit 2: Serious eye damage/eye irritation, Hazard Category 2	

Repr 1B: Reproductive toxicity, Hazard Category 1B

STOT RE 2: Specific target organ toxicity – Repeated exposure, Hazard Category 2