Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML
- · Article number: TD81260
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Tegee-dan

Helge Nielsens Allé 7 1A 8723 Løsning DENMARK

T: +45 7563 1370

F: +45 75631371

www.tegee-dan.dk

info@tegee-dan.dk

- · Further information obtainable from: QHSE Department
- · 1.4 Emergency telephone number: +45 7563 1370

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

R52/53-66: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment. Repeated exposure may cause skin dryness or cracking.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurised container.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

	Mineral oil	25-50%
	♦ Asp. Tox. 1, H304	
CAS: 74-98-6	propane	12.5-20%
EINECS: 200-827-9	F+ R12	
Index number: 601-003-00-5	6 Flam. Gas 1, H220	
Reg.nr.: 01-2119486944-21-xxxx	Press. Gas C, H280	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol	10-12.5%
EC number: 918-481-9	CAS nr. 71-43-2)	
Index number: 649-327-00-6	X Xn R65	
Reg.nr.: 01-2119457273-39-xxxx	<u>R6</u> 6	
	♦ Asp. Tox. 1, H304	
CAS: 106-97-8	butane	10-12.5%
EINECS: 203-448-7	F+R12	
Index number: 601-004-00-0	6 Flam. Gas 1, H220	
Reg.nr.: 01-2119474691-32-xxxx	Press. Gas C, H280	

- CD

(Contd. of page 1)

Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

	(C	ontd. of page 2)
CAS: 109-66-0	pentane	10-12.5%
EINECS: 203-692-4	X n R65	
Index number: 601-006-00-1	F+R12	
Reg.nr.: 01-2119459286-30-xxxx	N R51/53	
3	R66-67	
	♠ Flam. Liq. 2, H225	
	♦ Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	STOT SE 3, H336	
CAS: 75-28-5	isobutane	10-12.5%
EINECS: 200-857-2	▶ F+ R12	
Index number: 601-004-00-0	6 Flam. Gas 1, H220	
Reg.nr.: 01-2119485395-27-xxxx		
· Additional information: For the	wording of the listed risk phrases refer to section 16.	

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients	with lim	it values	that rea	เมเ่re mor	nitoring	at the	worknlace.
mgremenis	wiin iim	u vuiues	inui reg	une mon	uuvung	ui ine	workpince.

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- · Protection of hands: Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

(Contd. on page 5)

 Printing date 15.12.2014
 Version number 138
 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

	(Contd. of pag
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	< 0 °C (< 32 °F)
_	Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	10.9 Vol %
Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)
Density at 20 °C (68 °F):	0.675 g/cm³ (5.633 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	65.0 %
EU-VOC:	438.8 g/l
EU-VOC in %:	65.00 %
Solids content:	34.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

GE

Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50	LD/LC50 values relevant for classification:		
64742-48-	9 Naphtha ((petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)	
Oral	LD50	>15000 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rab)	
Inhalative	LC50 / 4 h	>4951 mg/m3 (rat)	
106-97-8 b	utane		
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)	
109-66-0 р	entane		
Oral	LD50	>16000 mg/kg (rat)	
Dermal	LD50	>2500 mg/kg (rat)	
		>5000 mg/kg (rabbit)	
Inhalative	LC50 / 4 h	>100 mg/m3 (rat)	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitisation: No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

40	uatic	toxicity:	

64742-48-9 Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)

LC50 / 96 h > 100 mg/l (crustacean (amphipod)) >100 mg/l (fish)

109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

LC50 / 96 h | 1-10 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

GB

 Printing date 15.12.2014
 Version number 138
 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

(Contd. of page 6)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- European waste catalogue
 20 01 13* solvents
 15 01 04 metallic packaging
 - · Uncleaned packaging:
 - · Recommendation: Non contaminated packagings may be recycled.

SECTION 14: Transport information		
· 14.1 UN-Number · ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
· IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	
Label	2.1	
IMDG, IATA		
Class	2.1	
Label	2.1	
14.4 Packing group	_	
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Gases.	
Danger code (Kemler):	-	
EMS Number:	F-D,S-U	
14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	e x II of Not applicable.	
Transport/Additional information:		
ADR		
Limited quantities (LQ)	IL	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity	

(Contd. on page 8)

Printing date 15.12.2014 Version number 138 Revision: 10.12.2014

Trade name: EXO 48 UNIVERSAL PTFE SPRAY 500 ML

	(Contd. of page 7)
· Tunnel restriction code	D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- R12 Extremely flammable.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

* Data compared to the previous version altered.