Contact Sheet



Europe



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

North America





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

Africa



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

Sparex Export Markets



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



SAFETY DATA SHEET

Version 1

Agri-Paint[®]

1. IDENTIFICATION

Product identifier

Product Name CO-OP Tractor Orange

Other means of identification

 Product Code
 S.118541

 UN/ID no
 UN1950

 SKU(s)
 None

Recommended use of the chemical and restrictions on use
Recommended Use
No information available.
Uses advised against
No information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co.

PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

Emergency Overview

Danger

Hazard statements

Causes serious eye irritation
May cause an allergic skin reaction
May cause genetic defects

May cause cancer

May cause respiratory irritation. May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Extremely flammable aerosol



Appearance No information available

Physical state Aerosol

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Use only outdoors or in a well-ventilated area

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

• Causes mild skin irritation

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Acetone	67-64-1	15 - 40	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	10 - 30	*
Propane	74-98-6	7 - 13	*
Butane	106-97-8	5 - 10	*
Ethylene Glycol Butyl Ether	111-76-2	1 - 5	*
Titanium dioxide	13463-67-7	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice Immediate medical attention is required. In case of accident or unwellness, seek medical

advice immediately (show directions for use or safety data sheet if possible). If symptoms

persist, call a physician.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician immediately. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and

upper eyelids. Consult a physician. If symptoms persist, call a physician.

Skin Contact Wash off immediately with plenty of water. Call a physician immediately. Wash off

immediately with soap and plenty of water while removing all contaminated clothes and

shoes. If skin irritation persists, call a physician.

Inhalation Immediate medical attention is required. Remove to fresh air. Avoid direct contact with skin.

Use barrier to give mouth-to-mouth resuscitation. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately. Move to fresh air in case of

accidental inhalation of vapors.

Ingestion Do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person. Drink 1 or 2 glasses of water. Clean mouth

with water and drink afterwards plenty of water. Call a physician.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Extremely flammable.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Use personal protective equipment as required.

Keep people away from and upwind of spill/leak.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or

tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up

Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust). Pick up and transfer to properly labeled containers. Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent

material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks,

flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. Use

personal protective equipment as required. Do not breathe

dust/fume/gas/mist/vapors/spray. Avoid breathing vapors or mists. Contents under

pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into

opening on top of can.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

containers tightly closed in a cool, well-ventilated place.

Incompatible materials Strong acids. Strong oxidizing agents. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m ³	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³ The	
		acetone STEL does not apply to the	
		cellulose acetate fiber industry. It is	
		in effect for all other sectors.	
		(vacated) STEL: 1000 ppm	
Propane	: See Appendix F: Minimal	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6	Oxygen Content, explosion hazard	TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
Butane	STEL: 1000 ppm explosion hazard	(vacated) TWA: 800 ppm	IDLH: 1600 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 800 ppm
			TWA: 1900 mg/m ³
Ethylene Glycol Butyl Ether	TWA: 20 ppm	TWA: 50 ppm	IDLH: 700 ppm
111-76-2		TWA: 240 mg/m ³	TWA: 5 ppm
		(vacated) TWA: 25 ppm	TWA: 24 mg/m ³
		(vacated) TWA: 120 mg/m ³	
		(vacated) S*	
		S*	
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³

13463-67-7		(vacated) TWA: 10 mg/m³ total dust	
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.

Skin and body protectionNo special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Aerosol

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point

Roiling point / boiling range

>= -42 °C / -44 °F

Boiling point / boiling range
Flash point

Evaporation rate
Flammability (solid, gas)

>= -42 °C / -44 °F
-104 °C / -155 °F
No information available
No information available

Flammability (solid, gas) No information Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific Gravity 0.78

Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity

No information available
No information available
No information available
No information available

Decomposition temperature

Kinematic viscosity

Dynamic viscosity

Explosive properties

No information available

Other Information

Softening pointNo information availableMolecular weightNo information available

Liquid Density 6.48 lbs/gal

Bulk density No information available

Percent solids by weight 22.8% Percent volatile by weight 42.8% Percent solids by volume 14.7% Actual VOC (lbs/gal) 2.8 Actual VOC (grams/liter) 332.2 EPA VOC (lbs/gal) 4.2 **EPA VOC (grams/liter)** 501.8 EPA VOC (lb/gal solids) 18.9

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
Butane 106-97-8	-	-	= 658 g/m³ (Rat) 4 h
Ethylene Glycol Butyl Ether 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg (Rabbit)	= 486 ppm (Rat) 4 h = 450 ppm Rat) 4 h
Titanium dioxide	> 10000 mg/kg (Rat)	-	-

Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg(Rabbit)	= 17.4 mg/L (Rat)4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m³(Rat)4 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m³ (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization
Germ cell mutagenicity
Carcinogenicity
No information available.
No information available.
No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethylene Glycol Butyl Ether 111-76-2	A3	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated

overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver

effects.

Target organ effects blood, Central nervous system, Eyes, Hematopoietic System, kidney, liver, Respiratory

system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg ppm mg/l

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

4.32% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Acetone	=	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	
Solvent Naphtha, Medium Aliphatic	450: 96 h Pseudokirchneriella	800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
Ethylene Glycol Butyl Ether	=	1490: 96 h Lepomis macrochirus	1000: 48 h Daphnia magna mg/L
111-76-2		mg/L LC50 static 2950: 96 h	EC50 1698 - 1940: 24 h Daphnia
		Lepomis macrochirus mg/L LC50	magna mg/L EC50

Ethyl Benzene	4.6: 72 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 2.6 - 11.3:	mykiss mg/L LC50 static 7.55 - 11:	EC50
	72 h Pseudokirchneriella	96 h Pimephales promelas mg/L	
	subcapitata mg/L EC50 static 1.7 -	LC50 flow-through 4.2: 96 h	
	7.6: 96 h Pseudokirchneriella	Oncorhynchus mykiss mg/L LC50	
	subcapitata mg/L EC50 static 438:	semi-static 32: 96 h Lepomis	
	96 h Pseudokirchneriella	macrochirus mg/L LC50 static 9.6:	
	subcapitata mg/L EC50	96 h Poecilia reticulata mg/L LC50	
		static 9.1 - 15.6: 96 h Pimephales	
		promelas mg/L LC50 static	
Methyl Ethyl Ketoxime	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
		760: 96 h Poecilia reticulata mg/L	
		LC50 static 320 - 1000: 96 h	
		Leuciscus idus mg/L LC50 static	
Mineral Spirits	-	2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Propane 74-98-6	2.3
Butane 106-97-8	2.89
Ethylene Glycol Butyl Ether 111-76-2	0.81
Ethyl Benzene 100-41-4	3.2
Methyl Ethyl Ketoxime 96-29-7	0.65

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number U002 U239

	Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
	Acetone	-	Included in waste stream:	-	U002
	67-64-1		F039		
	Ethyl Benzene	-	Included in waste stream:	-	-
L	100-41-4		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Acetone	Ignitable
67-64-1	
Ethyl Benzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no UN1950 Proper shipping name Aerosols Hazard class

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

UN1950, Aerosols, 2.1 Description

Emergency Response Guide 126

Number

TDG

UN/ID no UN1950 Proper shipping name Aerosols Hazard class 2.1

UN1950, Aerosols, 2.1 Description

MEX

UN/ID no UN1950 Proper shipping name Aerosols

Hazard class

UN1950, Aerosols, 2 Description

ICAO (air)

UN/ID no UN1950 Proper shipping name Aerosols Hazard class 2.1 **Special Provisions** A145, A167

Description UN1950, Aerosols, 2.1

IATA

UN Number UN1950

Aerosols, flammable Proper shipping name

Transport hazard class(es) 2.1 **ERG** Code 10L

Special Provisions A145, A167, A802

Description UN1950, Aerosols, flammable, 2.1

IMDG

UN Number UN1950 **UN** proper shipping name Aerosols Transport hazard class(es) EmS-No F-D, S-U

Special Provisions 63, 190, 277, 327, 344, 959 Description UN1950, Aerosols, 2

RID

UN/ID no UN1950 Proper shipping name Aerosols Transport hazard class(es) 2.1 Classification code 5F

Description UN1950, Aerosols, 2.1

ADR

UN Number UN1950 Proper shipping name Aerosols Transport hazard class(es) 2.1 Classification code 5F **Tunnel restriction code** (D)

Special Provisions 190, 327, 344, 625

Description UN1950, Aerosols, 2.1, (D)

Labels 2.1

ADN

Proper shipping name Aerosols
Transport hazard class(es) 2.1
Classification code 5F

Special Provisions 190, 327, 344, 625 **Description** UN1950, Aerosols, 2.1

Hazard label(s) 2.1 Limited quantity (LQ) 1 L

Ventilation VE01, VE04

15. REGULATORY INFORMATION

International Inventories

Complies **TSCA** Complies * **DSL/NDSL** Complies * **EINECS/ELINCS** Does not comply * **ENCS** Complies ³ **IECSC KECL** Does not comply * **PICCS** Does not comply * **AICS** Does not comply *

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Ethylene Glycol Butyl Ether	1.0
Ethyl Benzene	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard Yes
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ
Ethyl Benzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Hansa Orange (Orange 5) - 3468-63-1	Carcinogen
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen
	Developmental
	Male Reproductive
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Acetone 67-64-1	Χ	X
Propane 74-98-6	Χ	X
Butane 106-97-8	Χ	X
Ethylene Glycol Butyl Ether 111-76-2	Χ	X
Xylene 1330-20-7	X	X
Propylene Glycol Methyl Ether 107-98-2	X	X
Ethyl Benzene 100-41-4	X	X

Chemical name	Pennsylvania
Acetone	X
67-64-1	
Propane	X
74-98-6	
Butane	X
106-97-8	
Ethylene Glycol Butyl Ether 111-76-2	X
111-76-2	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no Hazardous Air Pollutants individually at 1% by weight, or greater.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 4 Instability 0 Physical and chemical

properties *

<u>HMIS</u> Health hazards 2 * Flammability 4 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date 21-May-2018

Revision Note

Revision Date 21-May-2018

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet