Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SAFETY DATA SHEET

Version 1

1. IDENTIFICATION

Product identifier Product Name

Cockshutt Red

Other means of identificationProduct CodeS.1SKU(s)S.1

S.118543 S.118542, S.118543

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co. PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749 Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin sensitization | Category 1 |
|------------------------|-------------|
| Germ cell mutagenicity | Category 1B |
| Carcinogenicity | Category 1B |
| Aspiration toxicity | Category 1 |
| Flammable liquids | Category 3 |

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



Appearance No information available

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Causes mild skin irritation
- Harmful to aquatic life with long lasting effects

· Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical name | CAS No | Weight-% | Trade Secret |
|-----------------------------------|------------|----------|--------------|
| Solvent Naphtha, Medium Aliphatic | 64742-88-7 | 30 - 60 | * |
| Calcium carbonate | 1317-65-3 | 3 - 7 | * |
| Xylene | 1330-20-7 | 1 - 5 | * |
| Ethyl Benzene | 100-41-4 | 0.1 - 1 | * |
| Titanium dioxide | 13463-67-7 | 0.1 - 1 | * |
| Mineral Spirits | 64742-48-9 | 0.1 - 1 | * |
| Methyl Ethyl Ketoxime | 96-29-7 | 0.1 - 1 | * |
| Neo C9-13 Acid, Cobalt Salts | 68955-83-9 | 0.1 - 1 | * |
| Cobalt neodecanoate | 27253-31-2 | 0.1 - 1 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice

Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

| Eye contact | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician. | |
|--|--|--|
| Skin Contact | Wash off immediately with plenty of water. Call a physician immediately. | |
| Inhalation | Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately. | |
| Ingestion | Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention. | |
| Self-protection of the first aider | Remove all sources of ignition. | |
| Most important symptoms and effe | ects, both acute and delayed | |
| Symptoms | No information available. | |
| Indication of any immediate medical attention and special treatment needed | | |
| Note to physicians | Treat symptomatically. | |
| 5. FIRE-FIGHTING MEASURES | | |

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

<u>Specific hazards arising from the chemical</u> Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| Personal precautions | Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. |
|-----------------------------------|---|
| Environmental precautions | |
| Environmental precautions | Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information. |
| Methods and material for containm | ent and cleaning up |
| Methods for containment | Prevent further leakage or spillage if safe to do so. |
| Methods for cleaning up | Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Cover liquid spill with |

sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

| Advice on safe handling | Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. |
|-------------------------|---|
| | grounded. Avoid contact with skin, eyes of clothing. |

Conditions for safe storage, including any incompatibilities

| Storage Conditions | Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away |
|--------------------|--|
| | from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). |
| | |

Incompatible materials Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| Chemical name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------|---------------------------|--|--|
| Calcium carbonate | - | TWA: 15 mg/m ³ total dust | TWA: 10 mg/m ³ total dust |
| 1317-65-3 | | TWA: 5 mg/m ³ respirable fraction | TWA: 5 mg/m ³ respirable dust |
| | | (vacated) TWA: 15 mg/m ³ total dust | |
| | | (vacated) TWA: 5 mg/m ³ respirable | |
| | | fraction | |
| Xylene | STEL: 150 ppm | TWA: 100 ppm | - |
| 1330-20-7 | TWA: 100 ppm | TWA: 435 mg/m ³ | |
| | | (vacated) TWA: 100 ppm | |
| | | (vacated) TWA: 435 mg/m ³ | |
| | | (vacated) STEL: 150 ppm | |
| | | (vacated) STEL: 655 mg/m ³ | |
| Ethyl Benzene | TWA: 20 ppm | TWA: 100 ppm | IDLH: 800 ppm |
| 100-41-4 | | TWA: 435 mg/m ³ | TWA: 100 ppm |
| | | (vacated) TWA: 100 ppm | TWA: 435 mg/m ³ |
| | | (vacated) TWA: 435 mg/m ³ | STEL: 125 ppm |
| | | (vacated) STEL: 125 ppm | STEL: 545 mg/m ³ |
| | | (vacated) STEL: 545 mg/m ³ | Ũ |
| Titanium dioxide | TWA: 10 mg/m ³ | TWA: 15 mg/m ³ total dust | IDLH: 5000 mg/m ³ |
| 13463-67-7 | C C | (vacated) TWA: 10 mg/m ³ total dust | 5 |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

| Eye/face protection | Tight sealing safety goggles. |
|--------------------------|---|
| Skin and body protection | No special technical protective measures are necessary. |
| Respiratory protection | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved |

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| Physical state Appearance Color | Liquid No information available No information available | Odor Odor threshold | No information available No information available |
|---|--|-------------------------|--|
| Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties | ValuesNo information availableNo information available>= 117 °C / 243 °F $39 °C / 102 °F$ No information availableNo | <u>Remarks • Method</u> | |
| Other Information | | | |
| Softening point Molecular weight Liquid Density Bulk density Percent solids by weight Percent volatile by weight Percent solids by volume Actual VOC (Ibs/gal) Actual VOC (grams/liter) EPA VOC (Ibs/gal) EPA VOC (grams/liter) EPA VOC (Ib/gal solids) | No information available No information available 8.14 lbs/gal No information available 53.9% 46.1% 42.3% 3.8 449.8 3.8 449.8 3.8 449.8 8.9 | | |

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

| Product Information | No data available |
|---------------------|--------------------|
| Inhalation | No data available. |
| Eye contact | No data available. |
| Skin Contact | No data available. |
| Ingestion | No data available. |

| Chemical name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|--|---------------------|---|--|
| Solvent Naphtha, Medium Aliphatic 64742-88-7 | > 25 mL/kg (Rat) | > 3000 mg/kg (Rabbit) | > 13 mg/L (Rat)4 h |
| Calcium carbonate 1317-65-3 | = 6450 mg/kg (Rat) | - | - |
| Xylene 1330-20-7 | = 3500 mg/kg (Rat) | > 4350 mg/kg (Rabbit)> 1700 mg/kg (Rabbit) | = 5000 ppm (Rat)4 h = 29.08 mg/L (Rat)4 h |
| Ethyl Benzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat)4 h |
| Titanium dioxide 13463-67-7 | > 10000 mg/kg (Rat) | - | - |
| Mineral Spirits 64742-48-9 | > 6000 mg/kg (Rat) | > 3160 mg/kg (Rabbit) | > 8500 mg/m³(Rat)4 h |
| Methyl Ethyl Ketoxime 96-29-7 | = 930 mg/kg(Rat) | 1000 - 1800 mg/kg (Rabbit) | > 4800 mg/m³(Rat)4 h |

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Sensitization Germ cell mutagenicity Carcinogenicity | No informati No informati No informati | on available. | | |
|--|--|---------------|------------------------|------|
| Chemical name | ACGIH | IARC | NTP | OSHA |
| Xylene 1330-20-7 | - | Group 3 | - | - |
| Ethyl Benzene 100-41-4 | A3 | Group 2B | - | Х |
| Titanium dioxide 13463-67-7 | - | Group 2B | - | Х |
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | - | Group 2B | Reasonably Anticipated | Х |
| Cobalt neodecanoate 27253-31-2 | - | Group 2B | Reasonably Anticipated | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

| IARC (International Agency for Res Group 2B - Possibly Carcinogenic to Group 3 - Not classifiable as a humar NTP (National Toxicology Program Resonably Anticipated - Reasonably | Humans n carcinogen |
|--|---|
| | ealth Administration of the US Department of Labor) |
| X - Present | |
| Reproductive toxicity | No information available. |
| STOT - single exposure | No information available. |
| STOT - repeated exposure | No information available. |
| Chronic toxicity | Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. |
| Target organ effects Aspiration hazard | Central nervous system, Eyes, kidney, Respiratory system, Skin. No information available. |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document $\,$ mg/kg $\,$ mg/l $\,$

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

Harmful to aquatic life with long lasting effects

| | 8.74% of the mixture consists of con | mponents(s) of unknown | hazards to the aquatic environment |
|--|--------------------------------------|------------------------|------------------------------------|
|--|--------------------------------------|------------------------|------------------------------------|

| Chemical name | Algae/aquatic plants | Fish | Crustacea |
|-----------------------------------|------------------------------------|--|-------------------------------------|
| Solvent Naphtha, Medium Aliphatic | 450: 96 h Pseudokirchneriella | 800: 96 h Pimephales promelas | 100: 48 h Daphnia magna mg/L |
| 64742-88-7 | subcapitata mg/L EC50 | mg/L LC50 static | EC50 |
| Xylene | - | 13.4: 96 h Pimephales promelas | 3.82: 48 h water flea mg/L EC50 |
| 1330-20-7 | | mg/L LC50 flow-through 13.5 - 17.3: | 0.6: 48 h Gammarus lacustris mg/L |
| | | 96 h Oncorhynchus mykiss mg/L | LC50 |
| | | LC50 23.53 - 29.97: 96 h | |
| | | Pimephales promelas mg/L LC50 | |
| | | static 2.661 - 4.093: 96 h | |
| | | Oncorhynchus mykiss mg/L LC50 | |
| | | static 780: 96 h Cyprinus carpio | |
| | | mg/L LC50 semi-static 780: 96 h | |
| | | Cyprinus carpio mg/L LC50 30.26 - | |
| | | 40.75: 96 h Poecilia reticulata mg/L | |
| | | LC50 static 19: 96 h Lepomis | |
| | | macrochirus mg/L LC50 7.711 - | |
| | | 9.591: 96 h Lepomis macrochirus | |
| | | mg/L LC50 static 13.1 - 16.5: 96 h | |
| | | Lepomis macrochirus mg/L LC50 | |
| | | flow-through | |
| Ethyl Benzene | 4.6: 72 h Pseudokirchneriella | 11.0 - 18.0: 96 h Oncorhynchus | 1.8 - 2.4: 48 h Daphnia magna mg/L |
| 100-41-4 | subcapitata mg/L EC50 2.6 - 11.3: | mykiss mg/L LC50 static 7.55 - 11: | EC50 |
| | 72 h Pseudokirchneriella | 96 h Pimephales promelas mg/L | |
| | subcapitata mg/L EC50 static 1.7 - | LC50 flow-through 4.2: 96 h | |
| | 7.6: 96 h Pseudokirchneriella | Oncorhynchus mykiss mg/L LC50 | |
| | subcapitata mg/L EC50 static 438: | semi-static 32: 96 h Lepomis | |
| | 96 h Pseudokirchneriella | macrochirus mg/L LC50 static 9.6: | |
| | subcapitata mg/L EC50 | 96 h Poecilia reticulata mg/L LC50 | |
| | | static 9.1 - 15.6: 96 h Pimephales | |
| Min anal Onivita | | promelas mg/L LC50 static | 0. C. OC. h. Chastana and an arises |
| Mineral Spirits | - | 2200: 96 h Pimephales promelas | 2.6: 96 h Chaetogammarus marinus |
| 64742-48-9 | 82,72 h Deemedeemus outerisetus | mg/L LC50 | mg/L LC50 |
| Methyl Ethyl Ketoxime | 83: 72 h Desmodesmus subspicatus | | 750: 48 h Daphnia magna mg/L |
| 96-29-7 | mg/L EC50 | promelas mg/L LC50 flow-through | EC50 |
| | | 760: 96 h Poecilia reticulata mg/L LC50 static 320 - 1000: 96 h | |
| | | | |
| 4 | l | Leuciscus idus mg/L LC50 static | |

Persistence and degradability

No information available.

Bioaccumulation

No information available.

| Chemical name | Partition coefficient |
|----------------------------------|-----------------------|
| Xylene 1330-20-7 | 3.15 |
| Ethyl Benzene 100-41-4 | 3.2 |
| Methyl Ethyl Ketoxime 96-29-7 | 0.65 |

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

| Disposal of wastes | Disposal should be in accordance with applicable regional, national and local laws and regulations. |
|------------------------|---|
| Contaminated packaging | Do not reuse container. |
| US EPA Waste Number | D001 U239 |

| Chemical name | RCRA | RCRA - Basis for Listing | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---------------|------|---------------------------|------------------------|-------------------------------|
| Xylene | - | Included in waste stream: | - | U239 |
| 1330-20-7 | | F039 | | |
| Ethyl Benzene | - | Included in waste stream: | - | - |
| 100-41-4 | | F039 | | |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical name | California Hazardous Waste Status |
|------------------------------|-----------------------------------|
| Xylene | Toxic |
| 1330-20-7 | Ignitable |
| Ethyl Benzene | Toxic |
| 100-41-4 | Ignitable |
| Neo C9-13 Acid, Cobalt Salts | Toxic |
| 68955-83-9 | |
| Cobalt neodecanoate | Toxic |
| 27253-31-2 | |

14. TRANSPORT INFORMATION

DOT

Marine pollutant

Not regulated This product contains a chemical which is listed as a marine pollutant according to DOT.

15. REGULATORY INFORMATION

International Inventories

| TSCA | Complies |
|---------------|-------------------|
| DSL/NDSL | Complies * |
| EINECS/ELINCS | Complies * |
| ENCS | Does not comply * |
| IECSC | Complies * |
| KECL | Does not comply * |
| PICCS | Does not comply * |
| AICS | Does not comply * |

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical name | SARA 313 - Threshold Values % |
|---------------|-------------------------------|
| Xylene | 1.0 |
| Ethyl Benzene | 0.1 |

SARA 311/312 Hazard Categories

| Yes |
|-----|
| Yes |
| Yes |
| No |
| No |
| |

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylene 1330-20-7 | 100 lb | - | - | Х |
| Ethyl Benzene 100-41-4 | 1000 lb | Х | Х | Х |

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Xylene | 100 lb | - | RQ 100 lb final RQ |
| 1330-20-7 | | | RQ 45.4 kg final RQ |
| Ethyl Benzene | 1000 lb | - | RQ 1000 lb final RQ |
| 100-41-4 | | | RQ 454 kg final RQ |

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical name | California Proposition 65 |
|-------------------------------------|---------------------------|
| Hansa Orange (Orange 5) - 3468-63-1 | Carcinogen |

| Ethyl Benzene - 100-41-4 | Carcinogen | |
|--|-------------------|--|
| Titanium dioxide - 13463-67-7 | Carcinogen | |
| Crystalline Silica - 14808-60-7 | Carcinogen | |
| Carbon Black - 1333-86-4 | Carcinogen | |
| Benzene(including benzene from gasoline) - 71-43-2 | Carcinogen | |
| | Developmental | |
| | Male Reproductive | |
| Cumene - 98-82-8 | Carcinogen | |
| Toluene - 108-88-3 | Developmental | |

U.S. State Right-to-Know Regulations

| Chemical name | New Jersey | Massachusetts |
|--|------------|---------------|
| Calcium carbonate 1317-65-3 | Х | X |
| Xylene 1330-20-7 | Х | X |
| Ethyl Benzene 100-41-4 | Х | X |
| Cobalt neodecanoate 27253-31-2 | Х | - |
| Neo C9-13 Acid, Cobalt Salts 68955-83-9 | Х | - |

| Chemical name | Pennsylvania |
|--------------------------------|--------------|
| Calcium carbonate 1317-65-3 | X |
| Xylene | X |
| 1330-20-7 | |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

| Chemical name | Weight % of HAPS in Product | Pounds HAPS / Gal Product |
|---------------|-----------------------------|---------------------------|
| Xylene | 2.27% | 0.18 |
| 1330-20-7 | | |

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| <u>NFPA</u> | Health hazards 2 | Flammability 2 | Instability 0 | Physical and chemical |
|------------------------|--------------------|-----------------|--------------------|-----------------------|
| | | | | properties - |
| HMIS | Health hazards 2 * | Flammability 2 | Physical hazards 0 | Personal protection X |
| Chronic Hazard Star Le | gend * = Chroni | c Health Hazard | | |

Revision Date Revision Note 21-May-2018

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet