# **Contact Sheet**



# **Europe**



Austria

Tel: +43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



France

Tel: +33 2987 89234 Sparex S.A.R.L. Zae De Ty Douar Commana 29450





Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Germany

Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Spain

Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)





Denmark

Tel: + 45 647 22287 Sparex Denmark Sparex Limited ApS Messevej 1 9600 Aars





Ireland

Tel: +353 51 855592 Sparex (Tractor Accessories) Ltd Grannagh Waterford Ireland



Poland

Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Tel: +44 1392 441338 Sparex Limited **Exeter Airport Devon** Exeter EX5 2LJ

# **North America**





Canada

Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119



USA

Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202

# **Africa**



South Africa

Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240 Cape branch

35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

# Australasia



Australia

Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345

# **Sparex Export Markets**



Export

Tel: +44 1392 441314 Sparex Limited **Exeter Airport** Devon Exeter EX5 2LJ



# SAFETY DATA SHEET

Version 1

# 1. IDENTIFICATION

Product identifier

**Product Name CAT New Yellow** 

Other means of identification

**Product Code** S.118717

SKU(s) S.118717, S.118719

Recommended use of the chemical and restrictions on use **Recommended Use** No information available. Uses advised against No information available

Details of the supplier of the safety data sheet

**Manufacturer Address** Van Sickle Paint Mfg. Co. PO Box 82222

Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

Chemtrec 1-800-424-9300 **Emergency Telephone** 

# 2. HAZARDS IDENTIFICATION

# Classification

## **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

# **Emergency Overview**

# Danger

#### Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways

Flammable liquid and vapor



Physical state Liquid Odor No information available Appearance No information available

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Wear protective gloves

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Use explosion-proof electrical/ ventilating/ lighting/ equipment

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

# **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

## Other Information

- · Causes mild skin irritation
- Harmful to aquatic life with long lasting effects
- · Harmful to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Solvent Naphtha, Medium Aliphatic	64742-88-7	15 - 40	*
Titanium dioxide	13463-67-7	1 - 5	*
Xylene	1330-20-7	1 - 5	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*
Cobalt 2-ethylhexanoate	136-52-7	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Stoddard Solvent	8052-41-3	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### Description of first aid measures

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

**Skin Contact** Call a physician immediately.

**Inhalation** Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Call a physician immediately.

**Ingestion** Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an

unconscious person. Get medical attention.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

# Specific hazards arising from the chemical

Flammable.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

## Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

**Environmental precautions** 

**Environmental precautions**Do not flush into surface water or sanitary sewer system. See Section 12 for additional

Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up

with inert absorbent material.

## 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

**Incompatible materials** Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m <sup>3</sup>
13463-67-7	_	(vacated) TWA: 10 mg/m³ total dust	-
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m <sup>3</sup>	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m <sup>3</sup>	
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m <sup>3</sup>	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>
		(vacated) TWA: 435 mg/m <sup>3</sup>	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m <sup>3</sup>
		(vacated) STEL: 545 mg/m <sup>3</sup>	
Stoddard Solvent	TWA: 100 ppm	TWA: 500 ppm	IDLH: 20000 mg/m <sup>3</sup>
8052-41-3		TWA: 2900 mg/m <sup>3</sup>	Ceiling: 1800 mg/m <sup>3</sup> 15 min
		(vacated) TWA: 100 ppm	TWA: 350 mg/m <sup>3</sup>
		(vacated) TWA: 525 mg/m <sup>3</sup>	_

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection**No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

No information available

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property
pH Values
No information available

Melting point / freezing point Boiling point / boiling range

Boiling point / boiling range >= 80 °C / 176 °F
Flash point 39 °C / 102 °F
Evaporation rate No information available

Remarks • Method

Flammability (solid, gas)

No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density
No information available
No information available
No information available
No information available

Specific Gravity 1.05

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available Dynamic viscosity **Explosive properties** No information available Oxidizing properties No information available

#### Other Information

Softening pointNo information availableMolecular weightNo information available

**Liquid Density** 8.79 lbs/gal

Bulk density No information available

Percent solids by weight 57.4% Percent volatile by weight 42.6% 42.3% Percent solids by volume Actual VOC (lbs/gal) 3.7 Actual VOC (grams/liter) 449 EPA VOC (lbs/gal) 3.7 EPA VOC (grams/liter) 449 EPA VOC (lb/gal solids) 8.9

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

# **Chemical stability**

Stable under recommended storage conditions.

# Possibility of hazardous reactions

None under normal processing.

## **Conditions to avoid**

Heat, flames and sparks.

# Incompatible materials

Chlorinated compounds.

# **Hazardous decomposition products**

Carbon oxides.

# 11. TOXICOLOGICAL INFORMATION

# Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

Eye contact No data available.

Skin Contact

No data available.

Ingestion

No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg(Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L (Rat) 4 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m³ (Rat) 4 h
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 10 mg/L (Rat) 1 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4800 mg/m³ (Rat) 4 h
Stoddard Solvent 8052-41-3	> 5000 mg/kg (Rat)	> 3000 mg/kg (Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity No information available.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Xylene 1330-20-7	-	Group 3	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	Х
Cobalt 2-ethylhexanoate 136-52-7	-	Group 2B	Reasonably Anticipated	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated

overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory

system, thyroid, testicles, and pituitary glands.

Target organ effectsLungs, Respiratory system.Aspiration hazardNo information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

# 12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

# **Ecotoxicity**

Harmful to aquatic life with long lasting effects

18.5% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Solvent Naphtha, Medium Aliphatic		800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50 mg/L LC50 static		EC50
Xylene	-	13.4: 96 h Pimephales promelas	3.82: 48 h water flea mg/L EC50
1330-20-7		mg/L LC50 flow-through 13.5 - 17.3:	0.6: 48 h Gammarus lacustris mg/L
		96 h Oncorhynchus mykiss mg/L	LC50
		LC50 23.53 - 29.97: 96 h	
		Pimephales promelas mg/L LC50	
		static 2.661 - 4.093: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 780: 96 h	
		Cyprinus carpio mg/L LC50 30.26 -	
		40.75: 96 h Poecilia reticulata mg/L	
		LC50 static 19: 96 h Lepomis	
		macrochirus mg/L LC50 7.711 -	
		9.591: 96 h Lepomis macrochirus	
		mg/L LC50 static 13.1 - 16.5: 96 h	
		Lepomis macrochirus mg/L LC50	
		flow-through	
Ethyl Benzene	4.6: 72 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 2.6 - 11.3:	mykiss mg/L LC50 static 7.55 - 11:	EC50
	72 h Pseudokirchneriella	96 h Pimephales promelas mg/L	
	subcapitata mg/L EC50 static 1.7 -	LC50 flow-through 4.2: 96 h	
	7.6: 96 h Pseudokirchneriella	Oncorhynchus mykiss mg/L LC50	
	subcapitata mg/L EC50 static 438:	semi-static 32: 96 h Lepomis	
	96 h Pseudokirchneriella	macrochirus mg/L LC50 static 9.6:	
	subcapitata mg/L EC50	96 h Poecilia reticulata mg/L LC50	
		static 9.1 - 15.6: 96 h Pimephales	
		promelas mg/L LC50 static	
Mineral Spirits	-	2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50
Methyl Ethyl Ketoxime	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
		760: 96 h Poecilia reticulata mg/L	
		LC50 static 320 - 1000: 96 h	
		Leuciscus idus mg/L LC50 static	

# Persistence and degradability

No information available.

# **Bioaccumulation**

No information available.

Chemical name	Partition coefficient
Xylene	3.15
1330-20-7	
Ethyl Benzene	3.2
100-41-4	
Methyl Ethyl Ketoxime	0.65
96-29-7	

Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

## Waste treatment methods

Disposal of wastes

Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** U220 U239 U019 U055 D001

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene	-	Included in waste stream:	-	U239
1330-20-7		F039		
Ethyl Benzene	-	Included in waste stream:	-	-
100-41-4		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethyl Benzene	Toxic
100-41-4	Ignitable
Cobalt 2-ethylhexanoate	Toxic
136-52-7	

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

Marine pollutant This product contains a chemical which is listed as a marine pollutant according to DOT.

# 15. REGULATORY INFORMATION

**International Inventories** 

TSCA Complies Complies \* **DSL/NDSL EINECS/ELINCS** Complies \* **ENCS** Does not comply \* Complies \* **IECSC** Complies \* **KECL** Complies \* **PICCS AICS** Does not comply \*

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

# **US Federal Regulations**

<sup>\*</sup> This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

# **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Xylene	1.0
Ethyl Benzene	0.1

# SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

#### **CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethyl Benzene 100-41-4	1000 lb	Х	Х	Х

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

	Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ī	Xylene	100 lb	=	RQ 100 lb final RQ
	1330-20-7			RQ 45.4 kg final RQ
Ī	Ethyl Benzene	1000 lb	<del>-</del>	RQ 1000 lb final RQ
	100-41-4			RQ 454 kg final RQ

# **US State Regulations**

## **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen
	Developmental
	Male Reproductive
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental

# U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Titanium dioxide	X	X
13463-67-7		
Xylene	X	X
1330-20-7		
Ethyl Benzene	X	X
100-41-4		
Cobalt 2-ethylhexanoate	X	-
136-52-7		

Chemical name	Pennsylvania
Titanium dioxide 13463-67-7	X
Xylene 1330-20-7	X

# **U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

# Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene	2.13%	0.19
1330-20-7		

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 2 Instability 0 Physical and chemical properties -

HMIS Health hazards 1 \* Flammability 2 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date 17-May-2018

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**