Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa

South Africa Cape - Tel: +27 00 21 887 3575 . KZN - Tel: + 27 31 573 1240

Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SAFETY DATA SHEET

Version 1

1. IDENTIFICATION

Product identifier Product Name

Fiat Allis Orange

Other means of identification Product Code SKU(s)

S.130380 S.130379, S.130380

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co. PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749 Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Aspiration toxicity	Category 1
Flammable liquids	Category 3

Emergency Overview

Danger

Hazard statements

May cause an allergic skin reaction May cause genetic defects May cause cancer May be fatal if swallowed and enters airways Flammable liquid and vapor



Appearance No information available

Physical state Liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use only non-sparking tools Take precautionary measures against static discharge Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Causes mild skin irritation

Harmful to aquatic life with long lasting effects

· Harmful to aquatic life

Unknown acute toxicity

12.21% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Solvent Naphtha, Medium Aliphatic	64742-88-7	30 - 60	*
Xylene	1330-20-7	1 - 5	*
Titanium dioxide	13463-67-7	1 - 5	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Mineral Spirits	64742-48-9	0.1 - 1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 - 1	*
Neo C9-13 Acid, Cobalt Salts	68955-83-9	0.1 - 1	*
Cobalt neodecanoate	27253-31-2	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

	continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
Self-protection of the first aider	Use personal protective equipment as required.
Most important symptoms and effe	ects, both acute and delayed
Symptoms	No information available.
Indication of any immediate medic	al attention and special treatment needed
Note to physicians	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

<u>Specific hazards arising from the chemical</u> Flammable.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Remove all sources of ignition. Use personal protective equipment as required.
Environmental precautions	
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional Ecological Information.
Methods and material for containme	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handlingAvoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray.
Do not eat, drink or smoke when using this product.Conditions for safe storage, including any incompatibilitiesKeep container tightly closed in a dry and well-ventilated place. Keep out of the reach of
children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights,
electric motors and static electricity).Incompatible materialsChlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylene	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7	-	(vacated) TWA: 10 mg/m ³ total dust	-
Ethyl Benzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
		(vacated) STEL: 545 mg/m ³	C C

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers Eyewash stations Ventilation systems.
Individual protection measures, suc	ch as personal protective equipment
Eye/face protection	Tight sealing safety goggles.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Liquid No information available No information available	Odor Odor threshold	No information available No information available
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit:	Values No information available No information available >= $117 \ ^{\circ}C / 243 \ ^{\circ}F$ 39 $\ ^{\circ}C / 102 \ ^{\circ}F$ No information available No information available No information available	<u>Remarks • Method</u>	
Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	No information available No information available 0.98 No information available No information available		
Other Information Softening point Molecular weight Liquid Density Bulk density Percent solids by weight Percent volatile by weight Percent solids by volume Actual VOC (lbs/gal) Actual VOC (grams/liter) EPA VOC (grams/liter) EPA VOC (lbg/gal)	No information available No information available 8.13 lbs/gal No information available 53.9% 46.1% 42.3% 3.8 449.9 3.8 449.9 8.9		

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Chlorinated compounds.

Hazardous decomposition products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information	on likelv	routes of	exposure
	•		

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 3000 mg/kg (Rabbit)	> 13 mg/L (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg(Rat)	> 4350 mg/kg (Rabbit)> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat)4 h = 29.08 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	> 8500 mg/m³ (Rat)4 h
Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4800 mg/m³(Rat)4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No information No information No information	on available.		
Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Ethyl Benzene 100-41-4	A3	Group 2B	-	Х
Neo C9-13 Acid, Cobalt Salts 68955-83-9	-	Group 2B	Reasonably Anticipated	Х
Cobalt neodecanoate 27253-31-2	-	Group 2B	Reasonably Anticipated	Х

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present Reproductive toxicity

Chronic toxicity

No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Ethylbenzene has been classified by the International Agency for Research on Cancer

Target organ effects Aspiration hazard	overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Lungs, Respiratory system. No information available.

(IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

This product contains a chemical which is listed as a marine pollutant according to DOT.

Ecotoxicity

Harmful to aquatic life with long lasting effects

15.78% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Solvent Naphtha, Medium Aliphatic		800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50
Xylene	-	13.4: 96 h Pimephales promelas	3.82: 48 h water flea mg/L EC50
1330-20-7		mg/L LC50 flow-through 13.5 - 17.3:	0.6: 48 h Gammarus lacustris mg/L
		96 h Oncorhynchus mykiss mg/L	LC50
		LC50 23.53 - 29.97: 96 h	
		Pimephales promelas mg/L LC50	
		static 2.661 - 4.093: 96 h	
		Oncorhynchus mykiss mg/L LC50	
		static 780: 96 h Cyprinus carpio	
		mg/L LC50 semi-static 780: 96 h	
		Cyprinus carpio mg/L LC50 30.26 -	
		40.75: 96 h Poecilia reticulata mg/L	
		LC50 static 19: 96 h Lepomis	
		macrochirus mg/L LC50 7.711 -	
		9.591: 96 h Lepomis macrochirus	
		mg/L LC50 static 13.1 - 16.5: 96 h	
		Lepomis macrochirus mg/L LC50	
		flow-through	
Ethyl Benzene	4.6: 72 h Pseudokirchneriella	11.0 - 18.0: 96 h Oncorhynchus	1.8 - 2.4: 48 h Daphnia magna mg/L
100-41-4	subcapitata mg/L EC50 2.6 - 11.3:	mykiss mg/L LC50 static 7.55 - 11:	EC50
	72 h Pseudokirchneriella	96 h Pimephales promelas mg/L	
	subcapitata mg/L EC50 static 1.7 -	LC50 flow-through 4.2: 96 h	
	7.6: 96 h Pseudokirchneriella	Oncorhynchus mykiss mg/L LC50	
	subcapitata mg/L EC50 static 438:	semi-static 32: 96 h Lepomis	
	96 h Pseudokirchneriella	macrochirus mg/L LC50 static 9.6:	
	subcapitata mg/L EC50	96 h Poecilia reticulata mg/L LC50	
		static 9.1 - 15.6: 96 h Pimephales	
		promelas mg/L LC50 static	
Mineral Spirits	-	2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50
Methyl Ethyl Ketoxime	83: 72 h Desmodesmus subspicatus	777 - 914: 96 h Pimephales	750: 48 h Daphnia magna mg/L
96-29-7	mg/L EC50	promelas mg/L LC50 flow-through	EC50
	-	760: 96 h Poecilia reticulata mg/L	
		LC50 static 320 - 1000: 96 h	
		Leuciscus idus mg/L LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
Xylene	3.15
1330-20-7	

Ethyl Benzene	3.2
100-41-4	
Methyl Ethyl Ketoxime	0.65
96-29-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U239

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream:	-	U239
Ethyl Benzene	-	F039 Included in waste stream:	-	_
100-41-4		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethyl Benzene	Toxic
100-41-4	Ignitable
Neo C9-13 Acid, Cobalt Salts	Toxic
68955-83-9	
Cobalt neodecanoate	Toxic
27253-31-2	

14. TRANSPORT INFORMATION

DOT

Marine pollutant

Not regulated

This product contains a chemical which is listed as a marine pollutant according to DOT.

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Does not comply *
ENCS	Does not comply *
IECSC	Complies *
KECL	Does not comply *
PICCS	Does not comply *
AICS	Does not comply *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	SARA 313 - Threshold Values %
Xylene	1.0
Ethyl Benzene	0.1

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethyl Benzene 100-41-4	1000 lb	X	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethyl Benzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

California Proposition 65
Carcinogen
Carcinogen
Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Xylene	Х	Х
1330-20-7		
Titanium dioxide	Х	Х
13463-67-7		
Ethyl Benzene	Х	Х

100-41-4		
Cobalt neodecanoate 27253-31-2	Х	-
Neo C9-13 Acid, Cobalt Salts 68955-83-9	Х	-

Chemical name	Pennsylvania
Xylene 1330-20-7	X
Titanium dioxide 13463-67-7	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene 1330-20-7	2.04%	0.17
1550 20 7		L

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 1	Flammability 2	Instability 0	Physical and chemical properties -
HMIS	Health hazards 1 *	Flammability 2	Physical hazards 0	Personal protection X
Chronic Hazard Star Le	egend *=Chroni	c Health Hazard		

Revision Date

24-Jan-2018

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet