Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa



Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SAFETY DATA SHEET

Section 1. Identification

AGCO Corporation 4205 River Green Parkwa Duluth, GA 30096	ły		y (CHEMTREC) chnical Information S Information	: 1-800-424-5 : 1-770-813-5 : 1-770-813-5
Product name :	Legacy Heavy Duty SAE 10W-30, 15W-4	40	SDS no.	: 1518-907980
Common name :	Diesel Engine Oil 10W-30, 15W-40		Revision date	: 08/07/2
Chemical name :	Lubricating oil.		Chemical formula	: Mi
Chemical family :	Hydrocarbon.			
Relevant identified uses	of the substance or mixture and uses	advised against		
Lubricant.				
	Section	2. Hazards identification		
OSHA/HCS status	: This material is conside	red hazardous by the OSHA Hazard	Communication Standard	(29 CFR 1910.1200)
Classification of the subs	stance or : SERIOUS EYE DAMAG	GE/ EYE IRRITATION - Category 2A		
GHS label elements				
Signal word	: Warning			
Hazard statements	: H319 - Causes serious	eye irritation.		
Hazard statements Precautionary statemer		eye irritation.		
	nts	eye irritation. Keep out of reach of children. If me	dical advice is needed, hav	ve product container
Precautionary statemer	nts : Read label before use. label at hand.			ve product container o
Precautionary statemer General	nts : Read label before use. label at hand. : Wear eye or face protect : IF IN EYES: Rinse cau	Keep out of reach of children. If me	nandling. s. Remove contact lenses,	
Precautionary statemer General Prevention	nts : Read label before use. label at hand. : Wear eye or face protect : IF IN EYES: Rinse cau	Keep out of reach of children. If mer ction. Wash hands thoroughly after h tiously with water for several minutes	nandling. s. Remove contact lenses,	
Precautionary statemer General Prevention Response	nts : Read label before use. label at hand. : Wear eye or face protect : IF IN EYES: Rinse cau do. Continue rinsing. If	Keep out of reach of children. If mer ction. Wash hands thoroughly after h tiously with water for several minutes	nandling. s. Remove contact lenses,	
Precautionary statemer General Prevention Response Storage	nts : Read label before use. label at hand. : Wear eye or face protect : IF IN EYES: Rinse cau do. Continue rinsing. If : Not applicable. : Not applicable.	Keep out of reach of children. If mer ction. Wash hands thoroughly after h tiously with water for several minutes	nandling. s. Remove contact lenses,	
Precautionary statemen General Prevention Response Storage Disposal Hazards not otherwise	nts : Read label before use. label at hand. : Wear eye or face protect : IF IN EYES: Rinse cau do. Continue rinsing. If : Not applicable. : Not applicable.	Keep out of reach of children. If men ction. Wash hands thoroughly after h tiously with water for several minutes eye irritation persists: Get medical a	nandling. s. Remove contact lenses,	, if present and easy t

Section 3. Composition/information of	on ingredients
---------------------------------------	----------------

Substance/mixture	: Mixture
Chemical name	: Lubricating oil.
Other means of identification	: Diesel Engine Oil 10W-30, 15W-40

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
Distillates (petroleum), hydrotreated light paraffinic	≥10 - ≤25	64742-55-8
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≥1 - ≤3	64742-65-0

Any concentration shown as a range is to protect confidentiality.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first ai	d measures		
Eye contact	: If material comes in contact with the eyes, immediately wash the eyes with large amounts of water for 15		
lub alatian	minutes, occasionally lifting the lower and upper lids. Get medical attention.		
Inhalation	 If person breathes in large amounts of material, move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the person warm and at rest. Get medical attention as soon as possible. 		
Skin contact	If the material comes in contact with the skin, wash the contaminated skin with soap and water promptly. If the material penetrates through clothing, remove the clothing and wash the skin with soap and water promptly. If irritation persists after washing, get medical attention immediately.		
Ingestion	: If material has been swallowed, do not induce vomiting. Get medical attention immediately.		
Most important symptoms/effec			
Potential acute health effects			
Eye contact	: Causes serious eye irritation.		
Inhalation	: No known significant effects or critical hazards.		
Skin contact	: No known significant effects or critical hazards.		
Ingestion	: No known significant effects or critical hazards.		
Over-exposure signs/symptom	<u>IS</u>		
Eye contact	: Adverse symptoms may include the following: pain or irritation, watering, redness.		
Inhalation	: Adverse symptoms may include the following: respiratory tract irritation, coughing.		
Skin contact	: Adverse symptoms may include the following: irritation, redness.		
Ingestion	: No known significant effects or critical hazards.		
Indication of immediate medic	al attention and special treatment needed, if necessary		
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 		
Specific treatments	: No specific treatment.		
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.		
See toxicological information	(Section 11)		
Section 5. Fire-fighting measures			

Extinguishing media	
Suitable extinguishing media	 Use water spray to cool fire exposed surfaces and to protect personnel. Foam, dry chemical or water spray (fog) to extinguish fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: Toxic fumes gases or vapors may evolve on burning.
Hazardous thermal decomposition products	: No specific data.
Special protective actions for fire-fighters	 When fighting fires wear full turnout gear and self contained breathing apparatus. Water may cause splattering. Material floats on water.
Special protective equipment for fire-fighters	: Not applicable.
	Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. Methods and materials for containment and cleaning up

Spill

: Contain with dikes or absorbent to prevent migration to sewers/streams. Take up small spill with dry chemical absorbent; large spills may require pump or vacuum prior to absorbent. May require excavation of severely contaminated soil.

Precautions for safe handling	
Protective measures	 Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
Conditions for safe storage, including any incompatibilities	: Do not store above the following temperature: 113°C (235.4°F). Odorous and toxic fumes may form from the decomposition of this product if stored at excessive temperatures for extended periods of time. Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Use appropriate containment to avoid environmental contamination.
	Section 8. Exposure controls/personal protection

Section 7. Handling and storage

Control parameters

E

Occupational exposure limits

Ingredient name		Exposure limits		
Distillates (petroleum), hydrotreated Distillates (petroleum), hydrotreated Distillates (petroleum), solvent-dewa	light paraffinic	OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist OSHA PEL (United States, 6/2016). TWA: 5 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist STEL: 10 mg/m³ 8 hours. ACGIH TLV (United States, 6/2016). TWA: 5 mg/m³ 8 hours. FORM STEL: 10 mg/m³ 15 minutes. Form: Mist STEL: 10 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist		
Appropriate engineering controls	: Use only with adequate ventilati	on.		
Environmental exposure controls	: Emissions from ventilation or we requirements of environmental p	ork process equipment should be checked to ensure they comply with the protection legislation.		
ndividual protection measures				
Hygiene measures		: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Ensure that eyewash stations and safety showers are close to the workstation location.		
Eye/face protection Skin protection		Recommended: Splash goggles and a face shield, where splash hazard exists.		

Hand protection	: 4 - 8 hours (breakthrough time): Nitrile gloves.
Body protection	: Recommended: Long sleeved coveralls.
Other skin protection	: Recommended: Impervious boots.
Respiratory protection	: If ventilation is inadequate, use a NIOSH-certified respirator with an organic vapor cartridge and P95 particulate filter.

Section 9. Physical and chemical properties

Appearance		Relative density	:	0.88 to 0.89
Physical state	: Liquid.	Evaporation rate	:	<1 (Butyl acetate = 1)
Color	: Amber.	Solubility	:	Insoluble in the following materials: cold water and hot water.
Odor	: Mild.	Solubility in water	:	Insoluble
Odor threshold	: Not available.	Partition coefficient: n-	:	Not available.
рН	: Not available.	octanol/water		

Melting point	: Not available.	Auto-ignition temperature	: >260°C (>500°F)
Boiling point	: Not available.	Decomposition temperature	: Not available.
Flash point	: Closed cup: >176.66°C (>350°F)	SADT	: Not available.
Flammability	: Not available.	Viscosity	: Not available.
Lower and upper	: Not available.	Vapor pressure	: <0.13 kPa (<1 mm Hg) (68°F)
explosive (flammable) limits		Vapor density	: Not available.

Section 10. Stability and reactivity

Reactivity Chemical stability Possibility of hazardous reactions		No specific test data related to reactivity available for this product or its ingredients. The product is stable. Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid Incompatible materials Hazardous decomposition products	:	No specific data. Reactive or incompatible with the following materials: oxidizing materials. Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), solvent-	LD50 Dermal	Rabbit	>5000 mg/kg	-
dewaxed heavy paraffinic	LD50 Oral	Rat	>5000 mg/kg	-
Irritation/Corrosion			L	
Skin				
Eyes	: Not hazardous (per manufacturer).			
Respiratory	: Not hazardous (per manufacturer).			
<u>Sensitization</u>				
Skin	: Not hazardous (per manufacturer).			
Respiratory	: Not hazardous (per manufacturer).			
Mutagenicity				
There is no data available.				
Carcinogenicity				
There is no data available.				
Reproductive toxicity				
There is no data available.				
<u>Teratogenicity</u>				
There is no data available.				
<u>Specific target organ toxicity (sin</u>	<u>gle exposure)</u>			
There is no data available.				
Specific target organ toxicity (rep	eated exposure)			
There is no data available.				
Aspiration hazard				
Name		Res	eult	

Name	Result
Distillates (petroleum), hydrotreated light paraffinic	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1

Information on the likely routes of : Dermal contact. Eye contact. Inhalation. Ingestion. exposure

Toxicity	
There is no data available.	
Persistence and degradability	
There is no data available.	
Bioaccumulative potential	
There is no data available.	
Mobility in soil	
Soil/water partition coefficient (Koc)	: There is no data available.
Other adverse effects	No known significant effects or critical hazards.
	Section 13. Disposal considerations
	protection and waste disposal legislation and any regional local authority requirements. Section 14. Transport information
DOT IDENTIFICATION NUMBER Not a	pplicable. DOT proper shipping name Not applicable.
DOT Hazard Class(es) Not applicable	. PG Not applicable. DOT EMER. RESPONSE GUIDE NO. Not available.
	Section 15. Regulatory information
U.S. Federal regulations :	 TSCA 4(a) final test rules: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters TSCA 8(a) PAIR: 2-Butenedioic acid (E)-, di-C8-18-alkyl esters TSCA 8(a) CDR Exempt/Partial exemption: Not determined United States inventory (TSCA 8b): Not determined. Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(sec-Bu and isooctyl) esters, zinc salts; Toluene; Benzene Clean Water Act (CWA) 311: Toluene; Benzene; Ethylenediamine; Vinyl acetate
lean Air Act Section 602 Class I Substa lean Air Act Section 602 Class II Substa lean Air Act Section 112(b) Hazardous	

SARA 302/304

Composition/information on ingredients

			SARA 302 TPQ		SARA 304 RQ	
Name	%	EHS	(lbs)	(gallons)	(lbs)	(gallons)
Ethylenediamine Vinyl acetate	≤0.1 ≤0.001	Yes. Yes.	10000 1000	1337.1 129	5000 5000	668.5 644.8

SARA 304 RQ

Hazard classifications

: 71876257.8 lbs / 32631821.1 kg [9740582.1 gal / 36872114.2 L]

SARA 311/312

: SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Composition/information on ingredients

Name	Classification	Classification			
Distillates (petroleum), hydro Distillates (petroleum), hydro Distillates (petroleum), solve	ASPIRATION HAZ	ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1			
SARA 313		subject to the reporting r -To-Know Act of 1986 an	equirements of SARA Section 313 of d of 40 CFR 372.		
Product name	CAS number	%			
Zinc compounds	Mixture	0.13 as Zinc			

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations		
Massachusetts	:	The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light paraffinic; Distillates (petroleum), solvent-dewaxed heavy paraffinic
New York	:	None of the components are listed.
New Jersey	:	The following components are listed: Distillates (petroleum), hydrotreated heavy paraffinic; Distillates (petroleum), hydrotreated light paraffinic; Distillates (petroleum), solvent-dewaxed heavy paraffinic
Pennsylvania	:	None of the components are listed.

California Prop. 65

WARNING: This product can expose you to Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Trace Metals, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www. P65Warnings.ca.gov.

Ingredient name	5	Maximum acceptable dosage level
Benzene Trace Metals	Yes.	Yes.
Toluene	-	- Yes.

Section 16. Other information

Revision date	:	08/07/2018	Supersedes
Revised Section(s)	:	1, 3, 8, 11, 15, 16.	Prepared by

: 08/25/2017

Prepared by

: KMK Regulatory Services Inc.

Notice to reader

THE INFORMATION CONTAINED IN THIS SDS RELATES ONLY TO THE SPECIFIC MATERIAL IDENTIFIED. IT DOES NOT COVER USE OF THAT MATERIAL IN COMBINATION WITH ANY OTHER THE INFORMATION CONTRINCT IN THIS SUS RELATES ONLY TO THE SPECIFIC MATERIAL DEVICE IN DOES NOT COVER USE OF THAT MATERIAL INCOMBINATION WITH AND OTHER MATERIAL OR IN ANY PARTICULAR PROCESS. IN COMPLIANCE WITH 29 C.F.R. 1910.1200(g), CHS HAS PREPARED THIS SDS IN SEGMENTS, WITH THE INTENT THAT THOSE SEGMENTS BE READ TOGETHER AS A WHOLE WITHOUT TEXTUAL OMISSIONS OR ALTERATIONS. CHS BELIEVES THE INFORMATION CONTAINED HEREIN TO BE ACCURATE, BUT MAKES NO REPRESENTATION, GUARANTEE, OR WARRANTY, EXPRESS OR IMPLIED, ABOUT THE ACCURACY, RELIABILITY, OR COMPLETENESS OF THE INFORMATION OR ABOUT THE FITNESS OF CONTENTS HEREIN FOR EITHER GENERAL OR PARTICULAR PURPOSES. PERSONS REVIEWING THIS SDS SHOULD MAKE THEIR OWN DETERMINATION AS TO THE MATERIAL'S SUITABILITY AND COMPLETENESS FOR USE IN THEIR PARTICULAR APPLICATIONS.