
Crosby Grade 100 Foundry Hooks



A-1359 Clevis Foundry Hook

- · Forged Alloy Steel Quenched and Tempered.
- Individually Proof Tested to 2-1/2 times the Working Load Limit with certification
- Each hook has a Product Identification Code (PIC) for material traceabilit, along with the size and the name Crosby.
- Suitable for use with Grade 100 and Grade 80 chain.
- Fatigue rated at 1-1/2 times the Working Load Limit at 20,000 cycles.
- "Look for the Platinum Color Crosby Grade 100 Alloy Products."
- Hook can be tip loaded at the reduced Working Load Limit, see below.

 Operator must ensure the load is retained properly in the hook.



A-1359 Clevis Foundry Hook

Chain Size			Working Load	Working Load		Dimensions (mm)							
(in)	(mm)	A-1359 Stock No.	Limit at Saddle of Hook (t)*	Limit at Tip of Hook (t)*	Weight Each (kg)	A	С	D	F	G	К	N	Deformation Indicators
1/4	7	1049907	2.0	1.0	0.98	159.0	111.3	122.4	63.5	28.7	22.4	39.9	88.9
5/16	8	1049911	2.6	1.3	0.93	159.0	111.0	122.4	63.5	28.7	22.4	39.9	88.9
3/8	10	1049916	4.0	2.0	1.95	197.1	140.7	147.8	76.2	35.1	33.0	47.8	101.6
1/2	13	1049925	6.8	3.4	3.62	238.3	169.4	178.8	88.9	41.4	38.1	57.2	114.3
5/8	16	1049934	10.3	5.1	6.44	285.8	195.1	207.5	101.6	55.6	44.5	64.3	127.0
3/4	18-20	1049943	16.0	8.0	11.2	366.5	248.7	245.1	127.0	61.0	55.9	86.1	152.4
7/8	22-23	10/19952	210	10.0	10.0	/12 B	270 0	280.2	130.7	78 N	69.1	95.0	165.1

^{*} Ultimate Load is 4 times the Working Load Limit.