Contact Sheet



Europe

Austria Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Italy

Tel: + 43 4212 6400 Sparex Austria Muraunberger Str Hurzendorf 9300



Portugal

Tel: +351 261 311107 Sparex Portugal, Importação e Comércio de Peças,Lda. Lugar da Espera 2565-716 Runa.



Belgium / Lux

Tel: + 32 58235140 Sparex Belgium Bvba Toevluchtweg 9 B-8620 Nieuwpoort



Tel: + 49 4282 93100 Sparex Germany Hansestrasse 03 Sittensen 27419



Netherlands

Tel: + 31 235 841 020 Sparex Holland BV Luzernestraat 19N 2153 GM Nieuw-Vennep



Tel: + 349 451 33524 Sparex Agrirepuestos, S.L. C/Jose Maria Iparraguirre No.15 B 01006 Vitoria-Gasteiz (Alava)



Canada Tel: + 905 786 277 Sparex Canada Highway No. 2 On Newcastle L1b 119





Tel: + 61 298 205 777 Sparex Australia Pty Ltd 81-83 Strzelecki Avenue, Sunshine West, VIC 3020



Tel: + 1 330 562 8150 Sparex US PO Box 510 Aurora, OH 44202



New Zealand

Tel: + 64 9634 4121 4 Princes Street Onehunga, Auckland 1345





Poland Tel: +48 61 816 19 37 61-168 ul. Rataje 164, Poznań



Africa



Cape branch 35 George Blake St, Plankenburg Stellenbosch 7600

KZN branch 59 Marseilles crescent Briardene Durban 4001

Sparex Export Markets

Export

Tel: +44 1392 441314 Sparex Limited Exeter Airport Devon Exeter EX5 2LJ

www.sparex.com



SAFETY DATA SHEET Cockpit Spray Gloss Lemon AEROSOL

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier		
Product name	Cockpit Spray Gloss Lemon AEROSOL	
Product number	SAPP0079A, CRFBU17, 79071081890, 79071120127, SAPP0121A, SAPP0079B	
Synonyms; trade names	3606605042482	
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.	
1.2. Relevant identified uses of	f the substance or mixture and uses advised against	
Identified uses	Dashboard Cleaner / Nettoyant plastiques	
1.3. Details of the supplier of the	ne safety data sheet	
Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com	
Contact person	Contact Email address: info@holtsauto.com	
1.4. Emergency telephone nun	nber	
Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167	
National emergency telephone number	http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national- helpdesks	
SECTION 2: Hazards identifica	ation	
2.1. Classification of the substa Classification (EC 1272/2008)	ance or mixture	
Physical hazards	Aerosol 1 - H222, H229	
Health hazards	Not Classified	
Environmental hazards	Not Classified	
Classification (67/548/EEC or 1999/45/EC)	F+;R12.	

2.2. Label elements

Pictogram



Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use.
Detergent labelling	5 - < 15% aliphatic hydrocarbons, < 5% perfumes, Contains preservation agents, Contains preservation agents
Supplementary precautionary statements	P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
Ingestion	Not relevant.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed	
SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
5.2. Special hazards arising from the substance or mixture	
Specific hazards	Risk of explosion if heated. Containers can burst violently or explode when heated, due to excessive pressure build-up.
5.3. Advice for firefighters	
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.
SECTION 6: Accidental release measures	

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

```
Methods for cleaning upWear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,<br/>clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames<br/>or other sources of ignition near spillage. Provide adequate ventilation. Wear protective<br/>clothing as described in Section 8 of this safety data sheet.
```

6.4. Reference to other sections

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Usage precautions	Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.
7.2. Conditions for safe storage	ge, including any incompatibilities
Storage precautions	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.
Storage class	Flammable compressed gas storage.
7.3. Specific end use(s)	
SECTION 8: Exposure Control	ols/personal protection
8.1. Control parameters	
Ingredient comments	WEL = Workplace Exposure Limits
8.2. Exposure controls	
Protective equipment	
Appropriate engineering controls	Provide adequate general and local exhaust ventilation.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). EN374
Other skin and body protection	Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
SECTION 9: Physical and Chemical Properties	

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Colourless.
Odour	Lemon.
Relative density	~0.85 @ °C
Solubility(ies)	Miscible with water. Alcohols.
9.2. Other information	
SECTION 10: Stability and re	activity
10.1. Reactivity	
10.2. Chemical stability	
Stability	Stable at normal ambient temperatures.
10.3. Possibility of hazardous	s reactions
10.4. Conditions to avoid	
Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.
10.5. Incompatible materials	
10.6. Hazardous decompositi	ion products
Hazardous decomposition products	Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).
SECTION 11: Toxicological ir	nformation
11.1. Information on toxicolog	gical effects
Inhalation	Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache. Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	
-	No harmful effects expected from quantities likely to be ingested by accident.
Skin contact	No harmful effects expected from quantities likely to be ingested by accident. Prolonged and frequent contact may cause redness and irritation.
Skin contact	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting.
Skin contact Eye contact	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting.
Skin contact Eye contact SECTION 12: Ecological Info	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity <u>12.1. Toxicity</u>	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity <u>12.1. Toxicity</u> 12.2. Persistence and degrad	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity <u>12.1. Toxicity</u> 12.2. Persistence and degrad 12.3. Bioaccumulative potenti	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity 12.1. Toxicity 12.2. Persistence and degrad 12.3. Bioaccumulative potenti 12.4. Mobility in soil	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.
Skin contact Eye contact SECTION 12: Ecological Info Ecotoxicity <u>12.1. Toxicity</u> <u>12.2. Persistence and degrad</u> <u>12.3. Bioaccumulative potenti</u> <u>12.4. Mobility in soil</u> <u>12.5. Results of PBT and vPv</u>	Prolonged and frequent contact may cause redness and irritation. Vapour or spray in the eyes may cause irritation and smarting. rmation The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment. dability ial <i>VB</i> assessment

Disposal methods	Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.
Waste class	WGK: 1 (Germany)
SECTION 14: Transport inform	nation
General	LIMITED QUANTITIES
14.1. UN number	
UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950
14.2. UN proper shipping nam	e
Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS
14.3. Transport hazard class(e	<u>es)</u>
ADR/RID class	2
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1
Transport labels	
14.4. Packing group	
ADR/RID packing group	N/A
IMDG packing group	N/A
ADN packing group	None
ICAO packing group	N/A
44 E. Environmental herorda	

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)
14.7. Transport in bulk accord	ing to Annex II of MARPOL and the IBC Code
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
SECTION 15: Regulatory infor	mation
	mation onmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

SECTION 16: Other information	
Revision date	14/08/2009
Revision	6
Supersedes date	01/02/2013
SDS number	13889
SDS status	Approved.
Risk phrases in full	R10 Flammable. R12 Extremely flammable. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	EUH066 Repeated exposure may cause skin dryness or cracking. H220 Extremely flammable gas. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.